View NSN Online: https://aerobasegroup.de/nsn/8030-00-664-7042 TRIRAM CORP -- PR-50-AF,TT-C-498B, COATING COMPOUND -- 8030-00-664-7042 Product ID:PR-50-AF,TT-C-498B, COATING COMPOUND MSDS Date:01/01/1985 FSC:8030 NIIN:00-664-7042 MSDS Number: BFKRW === Responsible Party === Company Name: TRIRAM CORP Emergency Phone Num:(617) 875-6600 CAGE:59983 === Contractor Identification === Company Name: TRIRAM CORP Address:721 WAVERLY ST Box:642 City:FRAMINGHAM State:MA ZIP:01701-8512 Country:US CAGE:59983 ======= Composition/Information on Ingredients ======== Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 **OSHA PEL:100 PPM** Ingred Name: ALUMINUM PIGMET PERCENT IS APPX Fraction by Wt: 11%. ========= Hazards Identification =============== Effects of Overexposure:MFR STATES SAME AS ANY PETROLEUM DERIVATIVE ========= First Aid Measures ====== First Aid:EYE: IMMEDIATELY FLUSH W/WATER AT LEAST 15 MIN. CALL MD. SKIN: WASH THOROUGHLY AFTER HANDLING ============= Fire Fighting Measures ======================== Flash Point:124F COC Extinguishing Media:CO*2, FOAM, SAND Fire Fighting Procedures: SIMILAR TO OTHER PETROLEUM PRODUCTS Unusual Fire/Explosion Hazard: NONE-SIMILAR TO OTHER PETROLEUM PRODUCTS ======== Accidental Release Measures =========== Spill Release Procedures: DRY W/NORMAL GARAG

MATL TAKING PRECAUTIONS AGAINST FIRE & INH HAZ.
======================================
Handling and Storage Precautions:AVOID EXCESSIVE HEAT OR MOISTURE
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NIOSH/MSHA APPRVD RESP PROT IF NEC Ventilation:LOCAL EXHST, YES Protective Gloves:IF NEC Eye Protection:GOGGLES IF NEC Oth
er Protective Equipment:AS REQ Supplemental Safety and Health MFR'S ADDRESS: TRITAM CORP, 721 WAVERY ST, FRAMINGHAM, MA 01701
======================================
HCC:F4 NRC/State Lic Num:NA Boiling Pt:B.P. Text:313F Spec Gravity:1.04 Evaporation Rate & Down Reference:0.06 Appearance and Odor:SILVER COLOR, ODOR SIMILAR TO MINERAL SPIRITS
========= Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES WATER Stabilit y Condition to Avoid:EXCESSIVE HEAT Hazardous Decomposition Products:NONE
========= Disposal Considerations ====================================
Waste Disposal Methods:DISPOSE IAW LOCAL, STATE, FED REG
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department

OIL DRY. MFR SUGGESTS USING MINERAL SPIRITS OR KEROSENE ON DRIED

E FLOOR CLEANER, I E SPEEDY

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liabi

lity for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.