

SENTRY PAINT & CHEMICAL CO, DARBY PA. 19023 -- PAINT HEAT RESISTING -- 8010-00-664-7468

=====  
Product Identification  
=====

Product ID:PAINT HEAT RESISTING

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-7468

MSDS Number: BFKTG

=== Responsible Party ===

Company Name:SENTRY PAINT & CHEMICAL CO, DARBY PA. 19023

Emergency Phone Num:215-GL9-5320

CAGE:GO855

=== Contractor Identification ===

Company Name:SENT

RY PAINT & CHEM CO

Address:MILL AND LAWRENCE ST

Box:City:DARBY

State:PA

ZIP:19023

Country:US

CAGE:GO855

Company Name:SENTRY PAINT AND CHEMICAL CO

Address:MILL AND LAWRENCE ST

Box:City:DARBY

State:PA

ZIP:19023

Country:US

CAGE:34346

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 23.0%

OSHA PEL:15MG/M3 DUST/5 FUME

ACGIH TLV:10MG/M3 DUST; 9192

Ingred Name:SILICONE ALKYD

Fraction by Wt: 18.0%

In

Product Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS #: SE7555000

Fraction by Wt: 59%

OSHA PEL: 100 PPM

===== Hazards Identification =====

Effects of Overexposure: DIZZINESS, HEADACHE AND NAUSEA

===== First Aid Measures =====

First Aid: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF BREATHING STOPS.

===== Fire Fighting Measures =====

Flash Point: 55F TCC

Lower Limits

: 1.0

Upper Limits: 7.0

Extinguishing Media: FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures: USE EQUIPMENT SUPPLIED AIR SUPPLY FOR ENCLOSED AREAS.

Unusual Fire/Explosion Hazard: COMBUSTIBLE LIQUID

===== Accidental Release Measures =====

Spill Release Procedures: CLEAN UP AS ANY FLAMMABLE LIQUID. AVOID SPARKS, USE DIRTY ABSORBENT IF POSSIBLE

===== Handling and Storage =====

Handling and Storage Precautions: AVOID OPEN FLAME AND HIGH TEMPERATURE

===== Exposure Controls/Personal Protection =====

Respiratory Protection: CARTRIDGE TYPE RESPIRATOR

Ventilation: LOCAL EXHAUST

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: F3

Boiling Pt: B.P. Text: 245-265F

Vapor Pres: 30

Vapor Density: 3.8

Spec Gravity: 1.0

Evaporation Rate & Reference: FASTER THAN NBUACT

Solubility in Water: NRG

Percent Volatiles by Volume: 61.0

===== Stability and Reactivity =====

ty Data =====

Stability Indicator/Materials to Avoid: YES

===== Disposal Considerations =====

Waste Disposal Methods: LET ABSORBENT DRY (EVAPORATE SOLVENT) AND  
DISPOSE OF IN CONTAINER

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be  
accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.