

EVERSEAL MFG CO -- GRAY ENAMEL, TT-P-91D TYPE 2, C-16376 -- 8010-00-664-9077

=====  
Product Identification  
=====

Product ID:GRAY ENAMEL, TT-P-91D TYPE 2, C-16376

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-9077

MSDS Number: BFKVQ

=== Responsible Party ===

Company Name:EVERSEAL MFG CO/RIDGEFIELD, NJ 07657

Emergency Phone Num:(201) 943-4986

CAGE:LO780

=== Contractor Identification ===

Company Name:EVER

SEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGEFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

Company Name:EVERSEAL MFG CO/RIDGEFIELD, NJ 07657

CAGE:LO780

=====  
Composition/Information on Ingredients  
=====

Ingred Name:RESIN (SEE SUPPLEMENTAL FOR INGREDIENTS)

Fraction by Wt: 27%

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 12%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ALIPHATIC NAPHTHA

Fra

ction by Wt: 27%  
ACGIH TLV:150 PPM

Ingred Name:AROMATIC NAPHTHA  
Fraction by Wt: 11%  
ACGIH TLV:100 PPM

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 11%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
Hazards Identification  
=====

Effects of Overexposure:DIZZINESS, NAUSEA, POSSIBLE UNCONSCIOUSNESS.  
IRRITATION TO SKIN & EYES.

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL  
RESPIRATION IF NEEDED. SKIN: WASH WITH SOAP & WATER. EYES: FLUSH  
WITH WATER. CONSULT PHYSICIAN.

=====  
Fire Fighting Measures  
=====

Flash Point:45F  
Lower Limits:1.0%  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL  
Fire Fighting Procedures:WATER NOT A SUITABLE EXTINGUISHING MEDIUM.  
WEAR SCBA.

=====  
Accidental Release Measures  
=====

Spill Release  
Procedures:ENSURE ADEQUATE VENTILATION. REMOVE IGNITION  
SOURCES. ABSORB SMALL SPILL ON DRY ADSOTION MATERIALS. USE SPARK -  
PROOF SCOOP FOR LARGER SPILLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID EXCESS HEAT. KEEP FROM OPEN  
IGNITION SOURCES.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:VAPOR CARTRIDGE MASK OR AIR-SUPPLIED HOOD.  
Ventilation:SUFFICIENT TO ENSURE LEL NOT A

CHIEVED.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:PROTECT SKIN WITH CLOTHING OR BARRIER CREAM.

Supplemental Safety and Health

MSDS DATE: 11/3/87. WT PER GAL: 8.1. ALSO CONTAINS: MINERAL SPIRITS  
(100412OMS) 2%, ETHYLENE GLYCOL MONOBUTYL ETHER (KJ85700) 10%.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:231-390F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:

72%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:CO, CO2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE PER LOCAL &  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The  
United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.