View NSN Online: https://aerobasegroup.de/nsn/6525-00-680-0496

EASTMAN KODAK COMPANY -- 146 5459, RAPID X-RAY DEVELOPER, PART C -- 6525-00-680-0496

Product ID:146 5459, RAPID X-RAY DEVELOPER, PART C

MSDS Date:03/01/1989

FSC:6525

NIIN:00-680-0496

Kit Part:Y

MSDS Number: BFLDY === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-72

2-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name: SODIUM HYDROXIDE (SARA III)

CAS:1310-73-2

RTECS #:WB4900000 Fraction by Wt: 100% OSHA PEL:2 MG/M3


ACGIH TLV:C 2 MG/M3; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt

======================================
LD50 LC50 Mixture:LD50 = 100 -200 MG/KG (RAT) Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:DUST IS VERY IRRITATING TO THE UPPER REAPIRATORY TRACT. PROLONGED EXPOSURE MAY RESULT IN BURNS. CONTACT WITH EYE/SKIN CAUSES BURNS. HARMFUL OR FATAL IF INGESTED. CAUSES SEVERE BURNS, SEVERE PAIN, VOMI TING, DIARRHE A AND SHOCK. Effects of Overexposure:SEE "HEALTH HAZARDS".
Medical Cond Aggravated by Exposure:NONE.
======================================
First Aid:EYES:FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MIN.SEE DOCTOR. SKIN:REMOVE CONTAMINATED CLOTHING & SHOES; INHALATION:REMOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION IF SYMPTO MS PERSIST; INGEST:DO NOT INDUCE VOMITING. IF CONSCIOUS GIVE ONE GLASS OF MILK OR WATER. NEVER GIVE A NYTHING BY
MOUTH TO AN UNCONSCIOUS PERSON. CALL A PHYSICIAN OR POISON CONTROL CENTER.
======================================
Flash Point:NONE Extinguishing Media:USE AGENT APPROPRIATE FOR SURROUNDING FIRE. Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. Unusual Fire/Explosion Hazard:REACTS WITH WATER. CAN REACT WITH METALS TO GENERATE FLAMMABLE HYDROGEN GAS. CONTACT WITH MOISTURE MAY GENERATE SUFFICIENT HEAT TO IGNITE COMBUSTIBLE MATERIALS.
======== Accidental Release Measures ==========
Spill Release Procedures:NEUTRALIZE WITH SODIUM BISULFATE. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.
============ Handling and Storage =============
Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED AND AWAY FROM WATER,ACIDS,COMMON METALS,ANHYDRIDES OR COMBUSTIBLE MATERIALS. Other Precautions:DO NOT ADD WATER TO A CLOSED CONTAINER SINCE THE

Qty:1000 LBS



Waste Disposal Methods: DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJE

CT

TO FEDERAL, STATE, OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.