View NSN Online: https://aerobasegroup.de/nsn/6750-00-680-7877

EASTMAN KODAK COMPANY -- 194 7738, HARDENER, PROCESS C-22, PART B -- 6750-00-680-7877

Product ID:194 7738, HARDENER, PROCESS C-22, PART B MSDS Date:01/01/1987 FSC:6750 NIIN:00-680-7877 Kit Part:Y MSDS Number: BFLHQ === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-722-51 51 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Ingred Name: FORMALDEHYDE (SARA III) CAS:50-00-0 RTECS #:LP8925000 Fraction by Wt: 35-40% OSHA PEL:SEE 1910.1048 ACGIH TLV:C 0.3 PPM; A2; 9293 EPA Rpt Qty:100 LBS

DOT Rp

t Qty:100 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III) CAS:67-56-1 RTECS #:PC1400000 Fraction by Wt: 10-15% Other REC Limits:ACGIH STEL 250 PPM OSHA PEL:S,200PPM/250STEL ACGIH TLV:S,200PPM/250STEL; 93 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 50-55%

Effects of

Overexposure:INHALE:IRRITNT(VAPOR);EYES:IRRITNT(VAPOR);BURNS(LIQUID);SKIN:IRRITNT(LIQ),ALLERGIC SKIN REACTION.

First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O*2 IF NEED;EYES:FLUSH W LG AMTS H*20 FOR 15 MIN;SKIN:FLUSH W LG AMTS H*20;INGEST:RINSE MOUTH;GET IMMEDIATE MEDICAL ATTN FOR EYES OR INGEST.

Flash Point:146F,63C TCC Lower Limits:7.0 Upper Limits:73 Extinguishing Media:WATER,DRY CHEMICAL,CARBON DIOXIDE. Fire Fighting Procedu res:WEAR SCBA & PROTECTV CLOTHG TO PREVENT SKIN/EYE CONTACT. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PROUDCTS.

Spill Release Procedures:WEAR APPROPRIATE PROTECTIVE EQUIPMENTS. STOP LEAK W/O RISK. DIKE LIQUID W/ABSORBENT & TRANSFER LIQ TO SALVAGE TANK. MFR SUGGESTS TO FLUSH MATERIAL TO AN ACID-FREE SEWER WITH LARGE AMOUNTS OF WATER.

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA.PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT.KEEP CONTAINERS TIGHTLY CLOSED.
Other Precautions:AVOID PROLONGED OR REPEATED CONTACT W CHEMICAL.REMOVE & WASH CONTAMINATED CLOTHING.MAINTAIN STRICT HYGIENE.KEEP COOL.STORE AWAY FROM HCL OR STRONG OXIDANTS.MAX TEMPERATURE: 120F.

========

Respiratory Protection:FOR EXPOSURE:SELF-CNTND BRTHG APP/APPR RESPIRATOR(ORGANIC VAPORS). Ventilation:MECHANICAL(GEN./LOCAL EXHAUST) Protective Gloves:IMPERVIOUS Eye Protection:SAFETY/CHEM GOGGLES. Other Protective Equipment:NORMAL FULL WORK CLOTHING COVERING ARMS,LEGS:NO SKIN CONTACT Supplemental Safety and Health KEY 1: X01; CSDS FROM KODAK DATED: 12/10/68, ADDENDUM TO MSDS DATED: 3/11/81; PH OF SOLN: 7.0; THIS IS PART B (FIXER) OF HARDENER KIT (KIT ALSO CONTAINS DE VELOPER, STOP BATH, BLEACH HARDENER-SEE OTHER PNI). KEY 1: F8

HCC:V4 Boiling Pt:B.P. Text:146F/63C Vapor Pres:17 Spec Gravity:1.08 Solubility in Water:COMPLETE Appearance and Odor:CLEAR AQUEOUS MIXTURE;TYPICAL FORMALDEHYDE ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES MINERAL ACIDS,STRONG OXIDIZERS Stability Condition

to Avoid:EXCESSIVE HEAT Hazardous Decomposition Products:THERMAL DECOMPOSITION WILL EMIT OXIDES OF CARBON.

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL.HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE,& LOCAL REGULATIONS.MFG SUGGESTS FLUSH TO SEWER WITH EXCESS WATER.

Disclaimer (provided with this information by the compiling agencies): This information is

formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.