View NSN Online: https://aerobasegroup.com/nsn/9160-00-685-0913 PHIPPS PRODUCTS CORP(DIST)EXXON CO., USA (MFR) -- UNIVOLT 60 -- 9160-00-685-0913 Product ID:UNIVOLT 60 MSDS Date:01/01/1985 FSC:9160 NIIN:00-685-0913 MSDS Number: BFLNT === Responsible Party === Company Name: PHIPPS PRODUCTS CORP(DIST) EXXON CO., USA (MFR) Emergency Phone Num:713-221-3424 CAGE:86511 === Contractor Identification === Company Name: PHIPPS PRODUCTS CORP Address: 186 LINCOLN ST SUITE 502 Box:City:BOSTON State:MA ZIP:02111-2403 Country:US Phone: OUT OF BUSINESS CAGE:86511 ======= Composition/Information on Ingredients ======== Ingred Name: PETROLEUM HYDROCARBONS Fraction by Wt: 100% ACGIH TLV:5MG/CUM(OIL MST Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD SKIN IRRITATION ===== First Aid:IF INGESTED DO NOT INDUCE VOMITING, CALL AP DOCTOR. REMOVE CONTAMINATED CLOTHING & WASH SKIN WITH SOAP & WATER.IN CASE OF CONTACT WITH EYES, FLUSH EYES WITH WATER UNTIL IRRITATION SUBSIDES Flash Point:320F COC Lower Limits: 1.0 Upper Limits:7.0 Extinguishing Media: FOAM, DRY CHEMICAL, CO\*2, WATER SPRAY OR FOG Fire Fighting Procedures: USE AIR-SUPPLIED RESCUE EQUIP. FOR ENCLOSED AREAS. Unusual Fire/Explosion

## Hazard: COOL EXPOSED CONTAINERS WITH WATER. DO NOT STORE OR MIX WITH STRONG OXIDANTS ======== Accidental Release Measures ============ Spill Release Procedures: RECOVER FREE LIQUID. ADD ABSORBENT TO SPILL AREA. VENTILATE ENCLOSED SPACES.KEEP PETROLEUM PRODUCTS OUT OF STREAMS AND WATERWAYS ============ Handling and Storage =========================== Handling and Storage Precautions: KEEP CONTAINERS CLOSED. KEEP AWAY FROM HEAT AND OPEN FLAME Other Precaution s:AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP & WATER AFTER CONTACT ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NORMALLY NOT NEEDED Ventilation:LOCAL EXHAUST, FACE VELOCITY > 60 FPM Protective Gloves: NOT REQUIRED

Ventilation:LOCAL EXHAUST, FACE VELOCITY >60 FPM
Protective Gloves:NOT REQUIRED
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:OIL-IMPERVIOUS APRON IF NEEDED
Supplemental Safety and Health
ITEM IS CLASS 1 OF SPEC

HCC:N1
Boiling Pt:B.P. Text:550-750F
Vapor Pres:0
Vapor Density:8.9
Spec Gravity:0.879
Evaporation Rate & Desire Reference: