

MALLINCKRODT INC.,SCIENCE PRODUCT DIVISION -- ALUMINUM SULFATE -- 6810-00-686-5892

=====  
Product Identification  
=====

Product ID:ALUMINUM SULFATE

MSDS Date:01/01/1987

FSC:6810

NIIN:00-686-5892

MSDS Number: BFLQN

=== Responsible Party ===

Company Name:MALLINCKRODT INC.,SCIENCE PRODUCT DIVISION

Emergency Phone Num:(314)982-5000

CAGE:62910

=== Contractor Identification ===

Company Name:MALLINCKRODT S

PECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALUMINUM SULFATE (SARA III)

CAS:10043-01-3

RTECS #:BD1700000

Fraction by Wt: >99%

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====  
Hazards Identification  
=====

Effects of Overexposure:INH:IRRIT,COUGHING,BRTHG

PROBLEM;ING:ABDOMINL

PAIN,GASTR-INTESTNL UPSET;SKIN/EYES:IRRIT,REDNESS ETC.

=====  
First Aid Measures  
=====

First Aid:INHAL:RMV TO FRESH AIR.GET MD FOR BREATHG

DIFFICULTY;INGEST:IMMED INDUCE VOMIT BY GIVING 2 LG OF

WATER/MILK.NOTHING BY MOUTH IF UNCONSCIOUS.GET MD IMMED;SKIN:WASH

W/SOAP & WATER.GET MD IF IRRIT OCCURS ;EYES:FLUSH W/H\*2O FOR 15

MIN.GET MED ATTN IMMED.

=====  
Fire Fighting Measures  
=====

Extinguishing Media:EXTINGUISH W. AGENT SUITABLE FOR SURROUNDING FIRE.  
Fire Fighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD  
BRTHG APP.  
Unusual Fire/Explosion Hazard:NOT CONSIDERED TO BE AN EXPLOSION HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:USE APPROPRIATE PROTECTV EQUIP.SWEEP UP OR  
VACUUM SPILLED MATL & PLACE IN A SUITABLE CONTNR FOR  
DISPOSAL.NEUTRALIZE THE RESIDUE W/SODA ASH.THEN FLUSH AREA W/PLENTY  
OF WATER.ADEQUATE VENTILATION IS REQ UIRED.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN TIGHTLY CLOSED CONTNRS AT  
COOL,DRY,VENTILATED PLACE.PROTECT AGAINST PHY DAMAGE.  
Other Precautions:AVOID BREATHING DUST.USE W/ADEQUATE VENTILATION.KEEP  
CONTAINRS CLOSED.WASH THOROUGHLY AFTER HANDLING.AVOID SKIN,EYES &  
CLOTHING CONTACT,BECOMES SLIPPERY WHEN ABSORBS MOISTURE.KEEP  
CLOSED/DRY.

===== Exposure Controls/Perso  
nal Protection =====

Respiratory Protection:SUPPLIED AIR RESPIR/SCBA; ESCAPE: GAS MASK  
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.  
Protective Gloves:IMPERVIOUS  
Eye Protection:GOGGLES/FACE SHIELD  
Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE  
WASH STATION  
Supplemental Safety and Health  
MSDS FM MFR DATED:8/13/85,CONFORMS TO OSHA HAZ COMM STD;ITEM IS TYPE  
II,CALSS 3 OF O-A-429.

===== Physical/Chemical Properties =====

HCC:N1  
Spec Gravity:1.61  
Solubility in Water:APPRECIABLE  
Appearance and Odor:WHITE GRANULAR POWDER,ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
ALKALIES,CORR MATL(H\*2O REACTIV MATL SUCH AS OLEUM)  
Hazardous Decomposition Products:TOXIC OXIDES OF SULFUR AT TEMP  
>76C(1400F).

===== Disposal Considerations =====

Waste Disposal Methods:LG QTY:SEND TO AN APPROVED WASTE FACILITY OR  
RECOVER.SM

QTY:MAY BE DISSOLVED IN WATER,TREATED WITH SODA ASH TO  
NEUTRALIZE & FLUSHED TO SEWER W/AMPLE WATER:ENSURE COMPLIANCE  
W/LOCAL,STATE,& FED REGS;CW A/CERCLA RQ=5000 LBS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any per  
son utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.