View NSN Online: https://aerobasegroup.de/nsn/6850-00-703-7406

ARDROX INC -- TRACER TECH D495C DEVELOPER -- 6635-00-703-7406

Product ID:TRACER TECH D495C DEVELOPER MSDS Date:04/01/1983 FSC:6635 NIIN:00-703-7406 MSDS Number: BFLYZ === Responsible Party === Company Name: ARDROX INC Address:16961 KNOTT AVE City:LA MIRADA State:CA ZIP:90638-6015 Country:US Info Phone Num:714-739-2821 Emergency Phone Num:714-739-2821 CAGE:23373 == = Contractor Identification === Company Name: BRENT AMERICA, INC. Address:16961 KNOTT AVE. Box:City:LA MIRADA State:CA ZIP:90638-6015 Country:US Phone:714-739-2821 CAGE:23373 Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Fraction by Wt: 51% OSHA PEL:350 PPM/450 STEL ACGIH TLV:350 PPM/450STEL;9192 EPA Rpt Qty:1000 LBS

Ingred Name:

DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1 POWER CONTENT Fraction by Wt: 10%

Ingred Name:SILICA, AMORPHOUS, DUST CAS:112945-52-5 RTECS #:VV7310000 Fraction by Wt: 0.4% OSHA PEL:6 MG/M3 ACGIH TLV:10 MG/M3; 8990

Ingred Name:METHYLENE CHLORIDE (SARA III) CAS:75-09-2 RTECS #:PA8050000 Fraction by Wt: 29% OSHA PEL:500 PPM/C,1000; Z2 ACGIH TLV:50 PPM, A2; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carci nogenicity:NTP:NO IARC:NO OSHA:NO Effects of Overexposure:ANAESTHETIC EFFECTS,HEADACHES,NAUSEA.

First Aid:EYE:FLUSH W/COPIOUS AMOUNT OF WATER;SKIN: WASH WITH SOAP & WATER;INHALE:REMOVE TO FRESH AIR,GIVE ARTIFICIAL RESPIRATION IF NEEDED;INGEST:DO NOT INDUCE VOMITING,CALL PHYSICIAN.

Flash Point:NONE Extinguishing Media:CO2, FOAM, DRY CHEM. Fire Fi ghting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: USE ABSORBENT MINERAL GRANULES, SAND OR EARTH TO REMOVE MAJORITY OF SPILLAGE. MOP UP USING A DETERGENT ANY POWDER REMAINING.

Handling and Storage Precautions: STORE AEROSOLS OUT OF DIRECT SUNLIGHT.

======= Exposure Controls/Personal Protection ==========

Res

piratory Protection:NO SPECIAL PROTECTIVE CLOTHING REQUIRED Ventilation:LOCAL EXHAUST Protective Gloves:NONE Supplemental Safety and Health KIT HAD 4 PARTS: P-149 PENETRANT, D-495C & D-493A DEVELOPERS,AND K410C REMOVER.THE KIT IS MARKETED BY THE COMPANY WHICH CHANGED NAME TO "ARDROX INC". PROPELLANT IN THE CAN WAS MIXTURE OF ISOBUTANE/PRO PANE GAS. KEY1:F1. CURRENT KIT HAS ESSENTIALLY THE SAME PARTS.THIS IS D495C. FSC 6635 FOR THIS PRODUCT IS NOW FSC 6850.

HCC:V3 Boiling Pt:B.P. Text:>104F/46C Vapor Pres:100 Spec Gravity:1.4 Solubility in Water:NEGLIGIBLE Appearance and Odor:SUSPENSION OF WHITE POWDER IN LIQUID. Percent Volatiles by Volume:60.0

SLOW HYDROLYSIS PRODUCES CORROSIVE ACID Stability Condition to Avoid:OPEN FLAMES Hazardous Decomposition Products:EXPOSURE TO HIGH TEMP.OR OPEN FLAME GENERATES HCL & PHOSG,CL Conditions

to Avoid Polymerization: OPEN FLAMES, WELDING ARCS

Waste Disposal Methods:USE SPECIALIST WASTE DISPOSAL COMPANY. FOR SMALL QUANTITIES,ALLOW SOLVENT TO EVAPORATE OUTSIDE THEN SWEEP UP POWDER REMAINING AND PUT IN TRASH.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatso ever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.