

ROYAL LUBRICANT CO,INC -- ROYCO 37 -- 9150-00-721-8570

===== Product Identification =====

Product ID:ROYCO 37

MSDS Date:01/01/1987

FSC:9150

NIIN:00-721-8570

MSDS Number: BFMGC

=== Responsible Party ===

Company Name:ROYAL LUBRICANT CO,INC

Emergency Phone Num:201-887-7410

CAGE:KO145

=== Contractor Identification ===

Company Name:ROYAL LUBRICANT CO.,INC.

Box:518

CAGE:KO145

Company Name:ROYAL LUBRICA

NTS COMPANY INC.

Address:215 MERRY LN

Box:518

City:EAST HANOVER

State:NJ

ZIP:07936

Country:US

Phone:973-887-7411/7410

CAGE:07950

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT REFINED,HYDROTREATED PETROLEUM DISTILLATES(CAS#  
64742-46-7,64742-53-6,64742-56-9)

Fraction by Wt: 87%

Ingred Name:CALCIUM HYDROXYSTEARATE CAS# 3159-62-4

Fraction by Wt: 11%

===== Hazards Identification =====

Effects of Overexposure:EYE:MI

LD IRRIT.INHAL,INGET:N/K.SKIN:INJECT IN  
SKIN DURING HI PRES USE CAUSE LOCAL NECROSIS.

=====  
First Aid Measures  
=====

First Aid:EYE:FLUSH W/ WATER FOR 15 MIN.CALL MD.INHAL:REMOVE TO FRESH  
AIR & GIVE O\*2.CALL MD.INGEST:DO NOT INDUCE VOMIT.GET MED  
ADVICE.SKIN:REMOVE CONTAM CLOTHING & WIPE OFF EXCESS.USE WATERLESS  
HAND CLEAN &/OR SOAP & WATER.CLEAN CLOTHING BEFORE REUSE.SUP DATA

=====  
Fire Fighting Measures  
=====

Flash Point:350F,152C PMCC  
Extinguishing Media:WATER FOG,DRY CHEM,CO\*2.DO NOT USE DIRECT STREAM OF  
WATER.  
Fire Fighting Procedures:USE NIOSH/MSHA APPVD SCBA IN CONFINED FIRE  
SPACE.  
Unusual Fire/Explosion Hazard:PRODUCT WILL FLOAT AND CAN IGNITE ON  
WATER SURFACE.COOL FIRE EXPO CONTNR,SURROUND EQUIP W/ WATER..

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SCOOP UP EXCESS GREASE.CLEAN AREA W/  
APPROPRIATE CLEANER.CLASSED AS OIL U  
NDER SECTION 311 OF THE CLEAN  
WATER ACT.SPILL ENTERING SURFACE WATERS DIRECTLY OR THROUGH SEWERS  
THAT CAUSE SHEEN MUST BE REPOR TED TO THE NATL RESPONSE  
CTR.800-424-8802.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN A COOL,DRY PLACE W/ ADEQUATE  
VENT.KEEP AWAY FROM OPEN FLAMES AND HI TEMP.MINIMIZE SKIN  
CONTACT.WASH W/ SOAP & WATER BEFORE EAT,DRINK,SMOKE.  
Other Precautions:WASH W/ SOAP & WATER BEFORE USING TOILE  
T.DISPOSE OF  
CONTAMINATED LEATHER ARTICLES THAT CAN NOT BE DECONTAMINATED.CALLED  
MFR FOR INFORMATON ON EMERGENCY NUMBER,VENT & EYE PROTECT.

=====  
Exposure Controls/Personal Protection  
=====

Ventilation:N/R(PER MFR)  
Protective Gloves:OIL RESISTANT  
Eye Protection:GOGGLES  
Other Protective Equipment:CLOTHING TO MINIMIZE SKIN CONTACT.  
Supplemental Safety and Health  
MSDS PREP:86178.FIRST AID:SKIN:IF IRRIT PERSISTS,CALL MD PROMPTLY TO  
PREVENT SERIOUS DAMAGE.DO NOT WAIT F

OR SYMPTOMS TO DEVELOP.NOTE TO  
MD:EMESIS INDUCTION NOT NEC FOR MOST OILS & GREASES.

===== Physical/Chemical Properties =====

HCC:V6

Solubility in Water:INSOLUBLE

Appearance and Odor:DARK AMBER,SMOOTH,SLIGHT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:AVOID HEAT,OPEN FLAME AND CONTACT WITH  
STRONG OXIDIZING AGNT

Hazardous Decompositio

n Products:MIX OF AIRBORN SOLID,LIQ

PARTICLES,GASES.CO\*2,UNK ORG COMPDS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN AN APPROPRIATE DISPOSAL FACILITY  
IN COMPLIANCE W/ LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or i

mplied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.