View NSN Online: https://aerobasegroup.de/nsn/8030-00-723-5345 COURTAULDS -- PR-812 -- 8030-00-723-5345 Product ID:PR-812 MSDS Date:01/01/1985 FSC:8030 NIIN:00-723-5345 Kit Part:Y MSDS Number: BFMMT === Responsible Party === Company Name: COURTAULDS Address:5430 SAN FERNANDO ROAD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info Phone Num:818-240-2060 Emergency Phone Num:800-424-9300 CHEMTREC/800-228-5635 CAGE:83574 == Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574 ======= Composition/Information on Ingredients ======== Ingred Name: METHYL EHTHYL KETONE RTECS #:PM7780000

RTECS #:PM7780000 Fraction by Wt: 18.0% ACGIH TLV:100 PPM

Ingred Name: METHYL ISOBUTYL KETONE (HEXONE) (SARA III)

CAS:108-10-1

RTECS #:SA9275000 Fraction by Wt: 18.0%

Other REC Lim

ACGIH TLV:50 PPM/75 STEL; 9394 EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
=========== Hazards Identification ============
Effects of Overexposure:HEADACHE, IRRITATION TO EYES AND SKIN
======================================
First Aid:SKIN-WASH THOROUGHLY WITH SOAP AND WATER, EYES-WASH OUT IMMEDIATELY WITH PLENTY OF WATER-SEE A PHYSICIAN, INHALATION-REMOVE AFFECTED PERSONNEL TO FRESH AIR
======== Fire Fighting Measures ============
Flash Point:30F,1C PMCC Lower Limits:1.8 Upper Limits:10
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
======== Accidental Release Measures ==========
Spill Release Procedures:ELIMINATE SOURCE OF IGNITION.WIPE UP EXCESS WITH RAGS.CLEAN AREA WITH METHYL KETONE. VENTILATE AREA TO DISPEL ODORS.
======================================
Handling and Storage Precautions:KEEP AWAY FROM H
EAT, SPARKS AND OPEN FLAMES. STORE IN TIGHTLY CLOSED CONTAINERS IN SHELTERED AREA Other Precautions:CONTAINS FLAMMABLE SOLVENT
====== Exposure Controls/Personal Protection ========
Respiratory Protection:AIR SUPPLIED RESPIRATOR WHEN NECESSARY Protective Gloves:YES Eye Protection:YES Supplemental Safety and Health KEY1:F3.
========= Physical/Chemical Properties ==========
HCC:F2 Boiling Pt:B.P. Text:176F,80C Vapor Pres:71 Vapor Density:2.50 Spec Gravity:1.

its:NONE RECOMMENDED

OSHA PEL:100 PPM

0900
Evaporation Rate & Reference: 5.7 ACETONE
Solubility in Water:INSOLUBLE
Appearance and Odor:THICK BLACK LIQUID, KETONE ODOR

Percent Volatiles by Volume:48.0

	Stability	/ and Reactivity	/ Data	
--	-----------	------------------	--------	--

Stability Indicator/Materials to Avoid:YES
DECOMPOSES WHEN EXPOSED TO STRONG OXIDIZERS
Stability Condition to Avoid:HEAT SPARKS AND OPEN FLAME
Hazardous Decomposition Products:CO2, ALDEHYDES

======= Disposal Considerations ===========

Wast

 $\Delta \Delta \Delta \Delta$

e Disposal Methods:TIGHTLY CLOSED CONTAINERS IN NORMAL TRASH. DO NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assu

me responsibility for the suitability of this information to their particular situation.