

PRATT AND LAMBERT-WICHITA DIV -- GLOSS GREEN 14050 -- 8010-00-753-4550

=====
Product Identification
=====

Product ID:GLOSS GREEN 14050

MSDS Date:01/01/1987

FSC:8010

NIIN:00-753-4550

MSDS Number: BFMYV

=== Responsible Party ===

Company Name:PRATT AND LAMBERT-WICHITA DIV

Emergency Phone Num:316-733-1361

CAGE:92216

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Address:945 BURL

INGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS LEL 1.10 VAPOR PRESSURE 3.20 I

Fraction by Wt: 40-5%

ACGIH TLV:500

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION:ANESTHETIC IRRITATION OF THE
RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACT

=====
First Aid Measures
=====

=====

First Aid:IN CASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER
WHILE REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH
AIR. CALL A DR. IF SYMPTONS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point:104 F

Lower Limits:1.10

Extinguishing Media:USE NAT'L FIRE PROTECTION ASSOC.(NFPA)CLASS B
EXTINGUISHERS

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE
AVAIL FOR FIREM

Unusual Fire/Explosion Hazard

:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE FROM HEAT,ELECTRICAL EQUIPMENT,SPARKS AND OPEN FLAMES. CLOSED

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT SURFACES,AND ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautio

ns:DO NOT STORE ABOVE 120F. STORE LARGE

QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID FREE

FALL OF LIQUID IN EXCESS OF A FEW INCHES.DO NOT FLAME CUT:BRAZE OR

WELD COATED MATERIAL WITHOUT BUREAU OF MINES APPROVED RESPIRATOR OR

AP

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN OUTDOOR OR OPEN AREAS,USE BUREAU OF MINES APPROVED MECHANICAL FIL

Ventil

ation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN

VOL

Protective Gloves:REQUIRED FOR PR

Eye Protection:SAFETY EYEWEAR DESIGNED

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO

CONTAMINATED CLOTHING.

Supplemental Safety and Health

INHALATION:ANESTHETIC,IRRITATION OF THE RESPIRATORY TRACT OR ACUTE

NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY

HEADACH,DIZZINESS,STAGGERING GAIT,CONFUSION,UNCONSCIOUSNESS OR

COMA. SKIN OR EYE

===== Physical/Chem

ical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373 F

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES,HEAT,AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL STATE,AND

FEDERAL REGULATIONS.INCINERATE IN APPROVED FACILITY.DO NOT

INCINERATE CLOSED CONTAINERS.

Disclaimer (pr

provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.