

MALLINCKRODT INC. SCIENCE PRODUCTS DIVISION -- METHYL ALCOHOL -- 6810-00-753-4783

=====
Product Identification
=====

Product ID:METHYL ALCOHOL

MSDS Date:04/06/1989

FSC:6810

NIIN:00-753-4783

MSDS Number: BFNCQ

=== Responsible Party ===

Company Name:MALLINCKRODT INC. SCIENCE PRODUCTS DIVISION

Address:PARIS BYPASS

Box:M

City:PARIS

State:KY

ZIP:40361

Country:US

Info Phone Num:314-982-5000

Emergency Ph

one Num:314-982-5000

CAGE:62910

=== Contractor Identification ===

Company Name:MALLINCKRODT SPECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: >99%

Other REC Limits:NONE

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DOT

Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 ORAL RAT=5628MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:SIGNS & SYMPTOMS OF

OVEREXPOSURE. CHRONIC:MARKED IMPAIRMENT OF VISION AND ENLARGEMENT OF THE LIVER HAS BEEN REPORTED.REPEATED OR PROLONGED EXPOSURE MAY CAUSE SKIN IRRITATION.

Effects of Overexposure:EYES:IRRI

TANT,EYE

LESIONS;SKIN:DEFATTING,DRYNESS,CRACKING;SKIN ABSORPTION:SYMPTOMS SIMILAR TO INHALATION;INHALATION:IRRITANT,TOXIC TO NERVOUS SYSTEM & OPTIC NERVE,HEADACHE,DROWINESS,NAUSEA,VOMIT,BLURRE D VISION,BLINDNESS,COMA,DEATH;INGESTION:SYMPTOMS SIMILAR TO INHALATION.CAN CAUSE BLINDNESS.FATAL DOSE=100-125ML

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN

DISORDERS OR EYE PROBLEMS OR IMPAIRED LIVER OR KIDNEY FUNCTION.

===== First Aid Measu

res =====

First Aid:EYES:FLUSH WITH PLENTY OF WATER.SEE DOCTOR

IMMEDIATELY;SKIN:REMOVE CONTAMINATED CLOTHING.WASH WITH PLENTY SOAP & WATER.IF IRRITATION PERSISTS,SEE DOCTOR;INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED.SEE DOCTOR;INGESTION:GIVE 2 GLASSES OF WATER & INDUCE VOMIT IMMEDIATELY.SEE DOCTOR .NOTHING BY MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:52.0F,1

1.1C

Autoignition Temp:Autoignition Temp Text:725F

Lower Limits:6.7

Upper Limits:36

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:VAPOR HEAVIER THAN AIR.CAN TRAVE ALONG GROUND

===== Accidental Release Measures =====

====

Spill Release Procedures:REMOVE IGNITIO SOURCES.VENTILATE.WEAR
RESPIRATORY PROTECTION & PROTECTIVE CLOTHING.ABSORB IN INERT
MATERIAL AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

==== Handling and Storage =====

Handling and Storage Precautions:PROTECT AGAINST PHYSICAL
DAMAGE.OUTSIDE OR DETACHED STORAGE PREFERRED.INSIDE STORAGE SHOULD
BE FOR FLAMMABLE LIQUID.SEPARATE FROM OXIDIZING MATERIALS.

Other Precautions:STORAGE & USE AREAS SHOULD B

E

NON-SMOKING.SPARKS-PROOF TOOLS & EXPLOSION-PROOF EQUIPMENT SHOULD
BE USED IN THE STORAGE & HANDLING AREA.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:RUBBER,NEOPRENE.

Eye Protection:GOGLES (DO NOT WEAR CONTACT LENSES)

Other Protective Equipment:RUBBER BOOTS,APRON OR COVERALLS. EYEWASH
STATION AND SA

FETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.REMOVE LAUNDER
CONTAMINATED CLOTHING.

Supplemental Safety and Health

NONE

==== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:=64.4C, 148.F

Melt/Freeze Pt:=-97.8C, -144.F

Vapor Pres:97

Vapor Density:1.1

Spec Gravity:0.8

Evaporation Rate & Reference:5.9 (BUTYL ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, COLORLESS LIQUID, CHAR. ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIZING AGENTS. WILL ATTACK SOME FORMS OF PLASTICS, RUBBER, COATING. MAY REACT WITH METALLIC AL TO FORM H² GAS.

Stability Condition to Avoid: HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products: CO, CO², FORMALDEHYDE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE AS HAZARDOUS WASTE IN A RCRA APPROVED

FACILITY. DO NOT FLUSH TO SEWER. COMPLY WITH ALL APPLICABLE FEDERAL, STATE & LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.