

FISKE BROTHERS REFINING CO. -- LUBRIPLATE MO-LITH NO.2 -- 9150-00-754-2595

=====  
Product Identification  
=====

Product ID:LUBRIPLATE MO-LITH NO.2

MSDS Date:01/01/1985

FSC:9150

NIIN:00-754-2595

MSDS Number: BFNMD

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO.

Emergency Phone Num:201-589-9150

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address

:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LITHIUM SOAP

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES

=

===== **Hazards Identification**=====

Effects of Overexposure:EYE/SKIN: IRRITATION

===== **First Aid Measures**=====

First Aid:EYE: FLUSH WITH WATER 15 MINUTES,CONSULT PHYSICIAN. SKIN:  
WASH WITH SOAP AND WATER.

===== **Fire Fighting Measures**=====

Flash Point:395F/201C (COC9

Lower Limits:1

Upper Limits:6

Extinguishing Media:CARBON DIOXIDE,FOAM,DRY CHEMICAL

Fire Fighting Procedures:SELF-CONT

BREATH APP,WATER FOG TO COOL EXPOSED

CONTAINERS.

Unusual Fire/Explosion Hazard:MAY FORM CO & SO\*2 IN COMBUSTION PROCESS.

===== **Accidental Release Measures**=====

Spill Release Procedures:WIPE UP WITH RAGS,CLEAN REMAINER WITH  
PETROLEUM SOLVENT.

===== **Handling and Storage**=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED,KEEP AWAY FROM  
HIGH HEAT & OPEN FLAME. NORMAL HYGIENE & SAFETY PRECAUTIONS SHOULD  
BE O

BSERVED IN HANDLING.

Other Precautions:REMOVE GREASE IMPRIGNATED CLOTHING,WASH THOROUGHLY  
AFTER EXPOSURE.

===== **Exposure Controls/Personal Protection**=====

Protective Gloves:OIL IMPERVIOUS

Eye Protection:GOGGLES

Supplemental Safety and Health

===== **Physical/Chemical Properties**=====

HCC:V6

Boiling Pt:B.P. Text:>650F/343C

Vapor Pres:12

Spec Gravity:0.94

Evaporation Rate & Reference:0.05 (N-BUTACET)

Solubility in Water:NEGLIGIBLE

Appearance

and Odor:GRAYISH BLACK GREASE WITH ADDITIVE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS

===== Disposal Considerations =====

Waste Disposal Methods:BY METHODS CONSISTENT WITH LOCAL,STATE AND  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. T

he United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.