

AMERON INDUSTRIAL COATINGS DIVISION -- 792-422 -- 8010-00-776-4633

=====
Product Identification
=====

Product ID:792-422

MSDS Date:01/01/1985

FSC:8010

NIIN:00-776-4633

MSDS Number: BFNZT

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone Num:714-529-4597

Emergency Phone Num:714-529-4597

CAGE:098

69

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

OSHA PEL:200 PPM/3

00 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ACETATE
RTECS #:AL1402500
ACGIH TLV:150 PPM

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
= Hazards Identification =====

Effects of Overexposure:EYE,THROAT,SKIN,LUNG
IRRITANT.DEPESSANT,COMA,UNCONCIOUSNESS,DIZZY

=====
First Aid Measures =====

First Aid:SKIN:WASH WELL. EYE:FLUSH W/WATER. INHAL:REMOVE TO FRESH
AIR.GIVE ARTIF.RESP.IF NEEDED,CALL DR. REMOVE CONTAMINATED
CLOTHING.

=====
Fire Fighting Measures =====

Flash Point:28F,-2.2C TCC
Lower Limits:1.2
Extinguishing Media:FOAM,DR

Y CHEM.,CARBON DIOXIDE

Fire Fighting Procedures:CLOSED CONTAINERS MAY BURST WHEN EXPOSED TO HEAT

Unusual Fire/Explosion Hazard:AVOID FIRE,HEAT,SPARKS,IGNITION SOURCES,STORAGE IN DIRECT SUNLIGHT.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA MECHANICALLY,KEEP FROM FLAME,FIRE,SPARKS,IGNITION SOURCES;DO NOT BREATHE VAPORS;CLEAN UP WITH ABSORBENT MATERIAL;USE NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED,UPRIGHT,AWAY FROM FIRE,FLAME,SPARKS,IGNITION SOURCES,DIRECT SUNLIGHT;DO NOT STORE ABOVE 120F.STORAGE NFPA CLASS I FLAMMABLE

Other Precautions:DO NOT INGEST.GROUND CONTAINERS WHEN POURING;DO NOT FLAME CUT,BRAZE,OR WELD COATED MATERIAL W/O ADEQUATE VENTILATION OR BUREAU OF MINES APPROVED RESPIRATOR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED BREATHING-APPARATUS FOR FIREMEN

Ventilation:LOCAL EXHAUST,MECHANICAL

Protective Gloves:YES

Eye Protection:GOGGLES/SAFETY GLASSES

Supplemental Safety and Health

BOILING RANGE IS 174-243F

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:174F,78C

Appearance and Odor:LIQUID,GREEN

Percent Volatiles by Volume:74.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition

to Avoid:FIRES,HEAT,HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:LOCAL,STATE AND FED.LAWS. DO NOT INCINERATE
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for
its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.