

3M COMPANY, -- SCOTCH-SEAL(R) TAMPER PROOF SEALANT 1252 -- 8030-00-779-4700

=====
Product Identification
=====

Product ID:SCOTCH-SEAL(R) TAMPER PROOF SEALANT 1252

MSDS Date:09/23/1986

FSC:8030

NIIN:00-779-4700

MSDS Number: BFPCS

=== Responsible Party ===

Company Name:3M COMPANY,

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-

733-1110

CAGE:76381

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

=====
Composition/Information on Ingredients
=====

Ing

red Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 26%
Other REC Limits:200 PPM
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ANTIMONY TRIOXIDE (SARA III)
CAS:1309-64-4
RTECS #:CC5650000
Fraction by Wt: 4%
Other REC Limits:5 MG/CUM SB
OSHA PEL:0.5 MG/M3 (SB)
ACGIH TLV:0.5 MG SB/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt:
Other REC Limits:
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-3
RTECS #:EV9580000
Fraction by Wt:
Other REC Limits:10 MG/CUM
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:ZINC OXIDE
CAS:1314-13-2
RTECS #:ZH4810000
Other REC Limits:10 MG/CUM
OSHA PEL:15MG/M3 TDUST/5 FUME
ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:BIS-TRIBUTYLTIN-N-OCTYLSUCCINATE
CAS:67701-37-5
Fraction

by Wt:
Other REC Limits:
OSHA PEL:
ACGIH TLV:

Ingred Name:MICA - SILICATES (< 1% CRYSTALLINE SILICA)
CAS:12001-26-2
RTECS #:VV8760000
OSHA PEL:20 MPPCF
ACGIH TLV:3 MG/M3 RDUST; 9293

Ingred Name:CHLORINATED PARAFFIN AND SALICYLIC ACID
Fraction by Wt:
Other REC Limits:
OSHA PEL:
ACGIH TLV:

Ingred Name:PHENOLIC RESIN AND EPOXY RESIN.
Fraction by Wt:
Other REC Limits:
OSHA PEL:
ACGIH TLV:

Ingred Name:SYNTHETIC RUBBER
Fraction by Wt:
Other REC Limits:
OSHA PEL:
ACGIH TLV:

=====
=== Hazards Identification =====

Effects of Overexposure:EYE:IRRIT.W/SMARTING,TEAR REDNESS.SKIN:IRRIT ON
PROLONGED/REPT CONTACT.INHAL:OVEREXPOS TO(MEK) VAPORS MAY CAUSE
RESP SYSTEM IRRIT. & TEMP NERVOUS SYSTEM IMPAIRMENT.SYMT OF
OVEREXPOS. DIZZY,HEADACHE.NA USEA NARC.EFFECTS.INGEST:IRRIT,W/
NAUSEA.VOMITING,OTHER: OVEREXPOS TO(MEK) ANIMAL,EMBRVO FETOTOXIC
EFFECTS.

===== First Aid Measures =====

First Aid:EYE:IMMED FLUS

H W/PLENTY OF H*2O FOR AT LEAST 15 MINUTES

.CALL PHYS.SKIN:WASH W/SOAP & H*2O.INHAL:PROVIDE FRESH AIR.IF NOT BREATHING GIVE ARTIFICIAL RESP.CALL A PHYS.INGEST: DO NOT INDUCE VOMITING.DRINK 2 GLASSES OF MILK OR H*2O CALLA PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:20F- -6.67C

Lower Limits:1.8

Upper Limits:11.5

Extinguishing Media:CO*2,FOAM, DRY CHEMICAL

Fire Fighting Procedures:FIRE FIGHTERS SHOULD BE EQUIPPED W / SCBA

Unusual Fire/Explosion Hazard:EXTREMELY FLAMMABLE.OVERHEATED,CLOSED CONTR ADJACENT TO FIRE COULD EXPLODE DUE TO PRESSURE BUILDUP.

=====
===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL IGNITION SOURCES. COLLECT SPILLED MATERIAL. CLEAN UP RESIDUE & PLACE IN CLOSED METAL CONTAINER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM ALL SOURCES OF IGNITION

. USE ONLY IN AREAS ADEQUATELY VENTILATED TO PREVENT VAPOR BUILD-UP.

Other Precautions:AVOID EYE CONTACT, PROLONGED BREATHING OF VAPORS & PROLONGED OR REPEATED SKIN CONTACT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP PROTECTION IF CONDITIONS REQUIRE

Ventilation:LOCAL EXHAUST

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

3-M I D NUMBER 62-1926-0304-1,62-1926-2604-2,62

===== Physical/Chemical Properties =====

HCC:F3
Boiling Pt:B.P. Text:176F (MEK)
Vapor Pres:80
Vapor Density:2.5
Spec Gravity:1.5
Evaporation Rate & Reference:2.7(ETHER = 1)
Solubility in Water:SLIGHT
Appearance and Odor:WHITE PASTE,SOLVENT ODOR
Percent Volatiles by Volume:26

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition
Products:CO,CO*2.SB204CANTIMONYTETRA
OXIDE)SB205(ANTIMONYPENTAOXIDE)

===== Disposal Considerations =====

Waste Disposal Methods:COMMERCIAL INCINERATION W/DESTRUCTION & REMOVAL
EFFICIENCY > 99.99%.OR RECLAMATION IS PREFERRED,OTHERWISE DISPOSE
IAW LOCAL & CURRENT REGS OR AUTHORITIES,U.S.EPA HAZ WASTE NUMBER
D001(IGNITABLE).

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The
United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.