

DOW CORNING CORPORATION -- DOW CORNING 200 FLUID, 200 CST -- 6850-00-781-3015

=====
Product Identification
=====

Product ID:DOW CORNING 200 FLUID, 200 CST

MSDS Date:01/01/1987

FSC:6850

NIIN:00-781-3015

MSDS Number: BFPFD

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Emergency Phone Num:(517) 496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Addre

ss:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:DOW CORNING 200 FLUID;(DIMETHYL SILOXANE) CAS #63148-62-9

CAS:63148-62-9

RTECS #:JT6484500

Fraction by Wt: 100%

=====
Hazards Identification
=====

=====

Effects of Overexposure:EYES:CAUSES TEMP DISCOMFORT;SKIN:SEVRL REPEATD
CONTCT CAUSES SLIGHT IRRIT;INHAL/INGEST:NOT KNOWN

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

=====

Flash Point:>600F/>315C (OC)
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*2O SPRAY TO COOL
CONTR.
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:USE APPROPRIATE PROTECTIVE EQUIPMENT. COVER
WITH SUITABLE ABSORBENT MATL. SHOVEL TO A CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED
Other Precautions:USE AT ELEVATD TEMP MAY REQ ADDED PRECAUTIONS.TRACES
OF FORMALDEHYDE & OTHER THERMAL DECOMPOSITION PRODUCTS MAY FORM AT
TEMP ABOVE 150C IN THE PRESENCE OF AIR.PROVIDE ADEQUATE
VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD

BE NEEDED

Ventilation:MFR RECOMMENDS MECHANICAL (GENERAL)

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Supplemental Safety and Health

MSDS FROM DOW CORNING DATED:1/20/86.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>300F/>149C

Vapor Pres: