

TESTING SYSTEMS,INC. -- FLUORO FINDER FL-2 -- 6850-00-782-2732

=====
Product Identification
=====

Product ID:FLUORO FINDER FL-2

MSDS Date:01/01/1985

FSC:6850

NIIN:00-782-2732

MSDS Number: BFPLN

=== Responsible Party ===

Company Name:TESTING SYSTEMS,INC.

Emergency Phone Num:201-767-7300

CAGE:28257

=== Contractor Identification ===

Company Name:TESTING SYSTEMS,INC.

CAGE:28257

=====
Composi
tion/Information on Ingredients
=====

Ingred Name:PIGMENTS

Fraction by Wt: 0.40%

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 90.0%

OSHA PEL:100 PPM

Ingred Name:SULFONAMIDE

CAS:63-74-1

RTECS #:WO8400000

ACGIH TLV:100PPM

Ingred Name:CHLORINATED HYDROCARBONS

Fraction by Wt: 4.0%

ACGIH TLV:200PPM

=====
Hazards Identification
=====

Effects of Overexposure:SKIN-DEFATTING

ACTION,IRRITATION,INHALATI

ON-HEADACHE,DROWSINESS,COMP,G.I.IRRIT;VOM
ITING,DIARRHEA.

=====
First Aid Measures
=====

First Aid:SKIN:FLUSH WITH WATER;INHALATION-REMOVE TO FRESH
AIR,ADMINISTER MOUTH TO MOUTH RESUSCITATION,INGESTION-CONTACT A
PHYSICIAN;EYES-FLUSH WITH WATER & SEEK MEDICAL ATTENTION

=====
Fire Fighting Measures
=====

Flash Point:185F TCC
Lower Limits:1.0
Upper Limits:7.5
Extinguishing Media:FOAM,DRY CHEMICAL,CO*2
Fire Fight
ing Procedures:USE SELF-CONTAINED BREATHING APPARATUS,COOL
CONTAINERS W/H*20
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG
OXIDANTS.COMBUSTIBLE LIQUID

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES.RECOVER FREE
LIQUID W/NON-SPARKING TOOLS.KEEP WELL VENTILATED.ADD ABSORBENT TO
REMAINING LIQUID.

=====
Handling and Storage
=====

Handling and Storage Precaut
ions:KEEP CONTAINERS CLOSED.KEEP AWAY FROM
HEAT,SPARKS & OPEN FLAME.AVOID STRONG OXIDIZING AGENTS
Other Precautions:AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.REMOVE
CONTAMINATED CLOTHING.WASH SKIN WITH SOAP & WATER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:HYDROCARBON VAPOR CANNISTER.
Ventilation:MECHANICAL,EXPLOSION PROOF,TO KEEP EQUIV.TO OUTDOOR VENTIL.
Protective Gloves:RUBBER IF REQD
Eye Protection:PROTECTIVE GOGGLES
Other Prote

Protective Equipment:HYDROCARBON-INSOLUBLE APRON IF NEEDED
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V4
Boiling Pt:B.P. Text:280F
Vapor Pres:8.0
Vapor Density:2.0
Spec Gravity:0.88
Solubility in Water:NEGLIGIBLE
Appearance and Odor:YELLOW OILY LIQUID WITH ALIPHATIC ODOR.
Percent Volatiles by Volume:90+

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:TEMP 600F,DECOMP OF DYE.
Hazardous Decomposition Products:CO IN CASE OF INCOMPLETE COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE ABSORBED LIQUID ACCORDING TO LOCAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.