

TRACER-TECH(CHEMICAL COMMODITIES) -- URESKO 149A -- 6850-00-782-2736

=====  
Product Identification  
=====

Product ID:URESKO 149A

MSDS Date:01/01/1985

FSC:6850

NIIN:00-782-2736

MSDS Number: BFPMQ

=== Responsible Party ===

Company Name:TRACER-TECH(CHEMICAL COMMODITIES)

Emergency Phone Num:213-876-2660

CAGE:LO965

=== Contractor Identification ===

Company Name:TRACER CORP

Address:3002 PENNSYLVANIA AVE

Box:City:SANTA MONICA

State:CA

ZIP:90404-4112

Country:US

CAGE:25858

Company Name:TRACER-TECH(CHEMICAL COMMODITIES)

CAGE:LO965

=====  
Composition/Information on Ingredients  
=====

Ingred Name:FLUORESCENT PENETRANT (TYPE NOT SPECIFIED)

Fraction by Wt: 100%

=====  
Hazards Identification  
=====

Effects of Overexposure:NONTOXIC-MEETS TOXICITY REQUIREMENT OF  
MIL-I-25135C

=====  
First Aid Measures  
=====

First

Aid:INHALATION:REMOVE TO FRESH AIR.INGESTION:RINSE MOUTH WITH  
WATER.SKIN:RINSE WITH WATER.EYES:FLUSH WITH WATER FOR AT LEAST 15  
MINS.SEE DOCTOR WHEN REQUIRED.

=====  
Fire Fighting Measures  
=====

Flash Point:>200F COC

Extinguishing Media:FREON

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:EVACUATE UNPROTECTED PE

RSONS.ELIM.IGNITION

SOURCES.STOP LEAK.H\*2O SPRAY COOL CONT/DIVERT SPILL FROM  
FIRE/HEAT.PROVIDE VENTILATION.ABSORB W/COMMERCIAL ABSORBENT,SHOVEL  
INTO METAL DRUMS-LG SPILL:DIKE W/ COMMERCIAL ABSORBENT,PUMP INTO  
COVERED DRUMS.

==== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW  
FIRE RISK AREA.PROTECT CONTAINERS FROM PHYSICAL DAMAGE.AVOID ANY  
PHYSICAL CONTACT.KEEP CONTAINERS TIGHTLY CLOSE

D

Other Precautions:REMOVE & WASH CONTAMINATED CLOTHING.MAINTAIN STRICT  
HYGIENE(WASH HANDS AFTER USE.)

==== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:N/A PER MANUFACTURER

Other Protective Equipment:NONE

Supplemental Safety and Health

SPEC GRADE VI.ABOVE ITEM IS FOR BULK.IN SPRAY CANS,AD PROPELLANT  
MATERIAL WHICH IS A COMBINATION OF ISOBUTANE & PROPANE.FLASH POINT  
DUE TO PROPELLANT 15-18F

==== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>350F

Vapor Pres: