View NSN Online: https://aerobasegroup.de/nsn/8010-00-787-8856

GROW GROUP INC U S PAINT DIV -- MIL-P-38336 -- 8010-00-787-8856

Product ID:MIL-P-38336 MSDS Date:01/01/1985 FSC:8010 NIIN:00-787-8856 MSDS Number: BFPVW === Responsible Party === Company Name: GROW GROUP INC U S PAINT DIV Address:831 S 21ST ST **City:SAINT LOUIS** State:MO ZIP:63103-3043 Country:US Info Phone Num: 314-621-0525 / FAX 314-621-0722 **Emergency Phone Num:314** -621-0525 CAGE:90608 === Contractor Identification === **Company Name: US PAINT CORPORATION** Address:831 SOUTH 21ST STREET Box:City:ST LOUIS State:MO ZIP:63103-3092 Country:US Phone:314-621-0525 CAGE:90608

Ingred Name:ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 24.0% OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III) CAS:110-80-5 RTECS #:KK8050000 Fraction by Wt: 1

2.0% OSHA PEL:S,200 PPM ACGIH TLV:S, 5 PPM; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
======================================
Effects of Overexposure: EYE AND UPPER RESPIRATORY IRRITANT
======================================
First Aid:IF EXPOSED TO EXCESS VAPOR,REMOVE TO FRESH AIR AND SEEK MED. ATT.IF SLASHED ON SKIN OR IN EYES,FLUS W/LG AMT OF WATER & SEEK IMMEDIATE MED ATT.IF INGESTED, DO NOT INDUCE VOMITING BUT SEEK
IMMED MEDICA L ATTN.
======================================
Flash Point:45 F TCC Lower Limits:2.6 Extinguishing Media:DRY CHEMICAL OR FOAM Unusual Fire/Explosion Hazard:DO NOT EXPOSE OR OPEN FLAME
======================================
Spill Release Procedures: AFFECTED AREA SHOULD BE TREATED WITH AN ABSORBING MATERIAL AND THEN PLACED IN A TIGHTLY CLOSED CONTAINER.
======================================
Handling and Storage Precautions: KEEP AWAY FROM EXCESS HEAT, SPARKS, AND FLAME.
======================================
Respiratory Protection: CHARCOAL BASE FOR SOLVENT VAPOR & NIOSH/MSHA APPROVED
Ventilation:LOCAL EXHAUST-SUFFICIENT TO KEEP AIR SUPPLY BELOW TLV Protective Gloves:RUBB OR POLYETH
Eye Protection:GOGGLES Other Protective Equipment:HYPERSENSITIVE PERSONS SHOULD WEAR PROTECTIVE CREAMS Supplemental Safety and Health VAPOR DENSITY IF HEAV

IER THAN AIR.

HCC:F2 Boiling Pt:B.P. Text:167 TO 279F Vapor Pres:3. Spec Gravity:1.01 Evaporation Rate & amp; Reference:1.0 N-BUAC Solubility in Water:APPRECIABLE Appearance and Odor:OFF WHITE-ALCOHOL Percent Volatiles by Volume:39.0

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS Stability Condition to Avoid:EXCESS HEAT Hazardous Decompositio n Products:NONE

Waste Disposal Methods: IN ACCORDANCE W/LOCAL STATE & FED CODES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this docum

ent should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.