

PRODUCTS/TECHNIQUES,INC. -- ANTIFOULING PPAINT PT-199 -- 8010-00-823-7911

=====  
Product Identification  
=====

Product ID:ANTIFOULING PPAINT PT-199

MSDS Date:01/01/1987

FSC:8010

NIIN:00-823-7911

MSDS Number: BFQYG

=== Responsible Party ===

Company Name:PRODUCTS/TECHNIQUES,INC.

Emergency Phone Num:213-770-3600

CAGE:06341

=== Contractor Identification ===

Company Name:PRODUCTS/TECHNIQUES INC

Address

:3271 S RIVERSIDE AVE

Box:City:RIALTO

State:CA

ZIP:92376

Country:US

Phone:909-877-3951

CAGE:06341

=====  
Composition/Information on Ingredients  
=====

Ingred Name:CUPROUS OXIDE

Fraction by Wt: 53.0%

ACGIH TLV:1.0 MG/CUM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 42.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL;9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====  
Hazards I

dentification =====

Effects of Overexposure:SKIN IRRITATION,EYE  
IRRITATION,ANESTHESIA,HEADACHE AND NAUSEA, DIZZINESS

===== First Aid Measures =====

First Aid:SKIN-USE SOAP AND WATER.EYES-INCASE OF EYE CONTACT FLUSH EYES  
WITH WATER, REMOVE VICTIM TO FRESH AIR AND RESTORE BREATHING IF  
REQUIRED.

===== Fire Fighting Measures =====

Flash Point:80 F, 27 C TCC

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM,CO\*2 STEAM,WATER-FOG,DRY CHEMICAL

Fire Fighting Procedures:DO NOT USE WATER, EXCLUDE AIR

Unusual Fire/Explosion Hazard:VAPOR FORMS EXPOOSIVE MIXTURES WITH AIR  
BETWEEN VEL AND LEL.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID OPEN FLAMES OR SPARK SOURCE-PROVIDE  
ADEQUATE VENTILATION,ABSORB WITH SWEEPING COMPOUND

===== Handling and Storage =====

Handling and Storage Precautions:

AVOID OPEN FLAMES AND SPARKS,AVOID  
SPLASH FILLING.STORE IN SEALED CONTAINERS.KEEP CONTAINERS CLOSED TO  
PREVENT MOISTURE ABSORPTION.

Other Precautions:AVOID SKIN & EYE CONTACT, WASH IMMEDIATELY AFTER  
CONTACT WITH SOAP & WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC MASK

Ventilation:LOCAL EXHAUST RECOM. APPROVED CLASS D FOR MECHANICAL

Protective Gloves:NOT REQUIRED

Eye Protection:SAFETY GLASSES DESIRED

Supplemental Safety an

d Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:281-294 F

Vapor Pres:6

Vapor Density:3.7

Spec Gravity:1.62

Evaporation Rate & Reference:0.59 BUTYL ACETATE

Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:EVAP

ORATE OR FLUSH WITH WATER TO OPEN WELL

VENTILATE D AREA-USE OIL SEWER IF AVAILABLE-REMOVE TO  
INCINERATOR,FOLLOW LOCAL EPA REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document sho  
uld seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.