

3M COMPANY - ADHESIVES COATINGS & SEALERS DIV -- SCOTCHWELD 1838B ADHESIVE TAN (PT B) -- 8040-00-823-7944

=====
Product Identification
=====

Product ID:SCOTCHWELD 1838B ADHESIVE TAN (PT B)

MSDS Date:01/01/1987

FSC:8040

NIIN:00-823-7944

MSDS Number: BFQYZ

==== Responsible Party ====

Company Name:3M COMPANY - ADHESIVES COATINGS & SEALERS DIV

Emergency Phone Num:612 733 1110 OP55

CAGE:04963

==== Contrac

tor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN

Fraction by Wt: 75.0%

Ingred Name:N-BUTYL GLYCIDYL ETHER (BGE)

CAS:2426-08-6

RTECS #:TX4200000

Fraction by Wt: 12.0%

OSHA PEL:50 PPM

ACGIH TLV:25 PPM; 9293

Ingred Name:SILICA, AMORPHOUS, DUST

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: 13.0%

OSHA PEL:6 MG/M3

ACGIH TLV:10 MG/M3; 8990

=====
Hazards Identification
=====

Effects of Overexposure:EYE:IRRIT ON DIRECT EXPOS. SKN:IRRIT,
SENSITIZATION POSSIBLE. INH:IRRIT NOSE, THROAT. INGES:NEG EFFECT.

=====
First Aid Measures
=====

First Aid:EYE:FLUSH 10 MIN W/WATER, CALL PHYS. SKN: WASH THOROUGHLY
SOAP & WATER. INH:REMOVE TO FRESH AIR. INGES:NO ACTION INDI

CATED.

=====
===== Fire Fighting Measures =====

Extinguishing Media:CO*2, DRY CHEMICAL, FOAM, WATER
Fire Fighting Procedures:USE SCBA IN FIRES INVOLVING THIS MATERIAL
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:OBSERVE ALL PRECAUTIONS. COLLECT SPILL & PLACE
IN APPROVED CONTAINER. CLEAN UP RESIDUE, WIPE UP AREA.

=====
===== Handling and Storage =====

=

Handling and Storage Precautions:USE ONLY IN WELL VENTILATED AREAS.
PREVENT CONTACT W/EYES & SKIN. WASH CONTAMINATED CLOTHING BEFORE
REUSE.AVOID INHL DUST.
Other Precautions:BUTYL GLYCIDYL ETHER IS SUSPECTED MUTAGEN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE DUST MASK WHEN GRINDING OR SAWING CURED
RESIN.
Ventilation:VENT CURING OVENS TO OUTDOORS. PROVIDE LOC EXH IN CONF
AREAS
Protective Gloves:USE IMPERVIOUS
Eye Protection
:USE SAFETY GLASSES
Other Protective Equipment:NONE
Supplemental Safety and Health
PART B OF TWO PART SCOTCHWELD 1838B/A TAN EPOXY ADHESIVE KT. UPDATE PER
3M MSDS 4NOV85 (OSHA) DOC# 1031426. 3M GENERIC ID# IS
62-1614-XXXX-X.FORMER P/N:SCOTCHWELD EC1838B TAN.

=====
===== Physical/Chemical Properties =====

HCC:V7
Spec Gravity:1.3
Viscosity:350000 CPS
Solubility in Water:VERY SLIGHT
Appearance and Odor:TAN, VISCOUS PASTE WITH LITTLE ODOR
Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: HCL, CO, CO*2, SMOKE PARTICLES WHEN
EXP EXCESS HEAT OR FLAME

===== Disposal Considerations =====

Waste Disposal Methods: CURED RESIN: DISPOSE IN APPD LANDFILL OR
INCINERATE PER REGS. INCINERATE UNCURED WASTE IN APPROVED DISPOSAL
FACILITY.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.