

FULLER-O'BRIEN CORP. -- FUNGICIDAL INSULATION VARNISH -- 5970-00-832-6950

=====
Product Identification
=====

Product ID:FUNGICIDAL INSULATION VARNISH

MSDS Date:06/03/1974

FSC:5970

NIIN:00-832-6950

MSDS Number: BFRQY

=== Responsible Party ===

Company Name:FULLER-O'BRIEN CORP.

Address:450 EAST GRAND AVENUE

City:SOUTH SAN FRANCISCO

State:CA

ZIP:94080-6207

Info Phone Num:415-761-2300

Emergency Phone

Num:415-761-2300

CAGE:3W855

=== Contractor Identification ===

Company Name:FULLER-O'BRIEN CORPORATION

Box:500

CAGE:3W855

Company Name:O BRIEN CORPORATION

Address:450 E GRAND AVE

Box:City:SOUTH SAN FRANCISCO

State:CA

ZIP:94080-6207

Country:US

CAGE:72556

=====
Composition/Information on Ingredients
=====

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 32%

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;9192

EPA Rpt Qty:5000 LBS

DOT Rpt

Qty:5000 LBS

Ingred Name:2-METHOXYETHANOL (EGME) (SARA III)

CAS:109-86-4

RTECS #:KL5775000

Fraction by Wt: 19%

OSHA PEL:S, 25 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:SALICYLANILIDE

CAS:87-17-2

RTECS #:VN7850000

Fraction by Wt: 3.8%

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

=====
===== Hazards Identification =====

R

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SEE SIGNS & SYMPTOMS OF OVEREXPOSURE.

Effects of Overexposure:NAUSEA,VOMITING,RINGING IN

EARS,DIZZINESS,HEADACHE,CONFUSION,RAPID PULSE & BREATHING,SWEATING.

Medical Cond Aggravated by Exposure:NONE NOTED.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH WITH WATER FOR 15 MINUTES.SEE DOCTOR;SKIN:REMOVE
CONTAMINATED CLOTHING & FLUSH SKIN WITH WATER;INHALATION:REMO
VE TO

FRESH AIR.SYMPTOMS WILL DISAPPEAR.TOXIC HAZARD IS RATED AS
LOW;INGESTION: SEE DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point:78F(26C)

Lower Limits:1.4

Extinguishing Media:DRY CHEMICAL,CO*2,FOAM

Fire Fighting Procedures:DO NOT USE WATER ON BURNING LIQUID. WEAR SCBA
& PROTECTIVE CLOTHING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR. CAN TRAVEL A
LONG DISTANCE & FLASHBACK.

=====

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB IN INERT MATERIAL & PLACE IN APPROPRIATE DISPOSAL COVERED METAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINER CLOSED TIGHTLY WHEN NOT IN USE. DO NOT STORE ABOVE 120F.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATOR FOR SPRAY APPLICATION.

Ventilation: LOCAL EXHAUST OR OPEN AIR.

Protective Gloves: RECOMMENDED FOR PROLONGED EXPOSURE.

Eye Protection: GOGGLES RECOMMENDED FOR PROLONGED EXPSRE

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: V3

Boiling Pt: B.P. Text: 244-290F

Decomp Temp: Decomp Text: 700F(371C)

Vapor Density: >1

Spec Gravity: 0.98

Evaporation Rate & Reference: