

AMERICAN WRITING INK. -- VV-L-820C;LUBRICATING OIL,GENERAL PURPOSE. -- 9150-00-836-8641
===== Product Identification =====

Product ID:VV-L-820C;LUBRICATING OIL,GENERAL PURPOSE.

MSDS Date:05/03/1987

FSC:9150

NIIN:00-836-8641

MSDS Number: BFRWH

=== Responsible Party ===

Company Name:AMERICAN WRITING INK.

Address:35 FARNSWORTH STREET

City:BOSTON

State:MA

ZIP:02210-1210

Country:US

Info Phone Num:617-

482-9167

Emergency Phone Num:617-482-9167

CAGE:82956

=== Contractor Identification ===

Company Name:AMERICAN INK AND OIL CORP

Address:33 ENDICOTT STREET

Box:City:NORWOOD

State:MA

ZIP:02062-3006

Country:US

Phone:781-762-0026 / FAX: 781-762-1617

CAGE:82956

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

===== Hazards Ide

ntification =====

Health Hazards Acute and Chronic:ACUTE:OIL MIST IS IRRITATING TO EYES,SKIN AND RESPIRATORY TRACT,REDNESS/DRYING. CHRONIC:MILD IRRITATION.

Effects of Overexposure:PROLONGED/REPEATED SKIN CONTACT MAY CAUSE MILD SKIN IRRITATION.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

===== First Aid Measures =====

First Aid:SKIN-WASH W/SOAP & WARM WATER. EYES-FLUSH W/WATER 15 MIN.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:320F,160C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:FOAM,DRY CHEM,CARBON DIOXIDE,WATER SPRAY/FOG

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE W/STRONG OXIDANTS LIKE OXYGEN OR CHLORINE.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LIQ. ADD ABSORBENT (SAND,ETC) TO SPILL AREA. KEEP OUT OF SEWER & WATERCOURSES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTRS CLOSED WHEN NOT IN USE. DO NOT HANDLE/STORE NEAR HEAT,SPARKS,OPEN FLAME,STRONG OXIDANTS. AVOID BREATHING OIL MIST.

Other Precautions:LAUNDER CONTAM CLOTHING AFTER USE. DISCARD OIL SOAKED SHOES. WASH SKIN THOR

ROUGHLY W/SOAP & WATER AFTER USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREA USE AIR-SUPPLIED RESPIR.

Ventilation:LOCAL OR MECH W/>60 FPM FACE VELOCITY.

Protective Gloves:CHEM RESISTANT

Eye Protection:SPLASH GOGGLES/FACE SHILD

Other Protective Equipment:CHEM RESIST APRON & OTHER CLOTH TO AVOID
PROLONGED EXPOS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling P

t:B.P. Text:540F/282C

Vapor Pres:11

Spec Gravity:0.9

Evaporation Rate & Reference: