View NSN Online: https://aerobasegroup.de/nsn/6750-00-837-7257

EASTMAN KODAK CO. -- 140 8988, HC-110 DEVELOPER (PRE 9/85) -- 6750-00-837-7257

============= Product Identification ========================

Product ID:140 8988,HC-110 DEVELOPER (PRE 9/85)

MSDS Date:06/18/1980

FSC:6750

NIIN:00-837-7257

MSDS Number: BFRWX === Responsible Party ===

Company Name: EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:716-722-5151

Emergency Phone Nu

m:716-722-5151 CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name: HYDROQUINONE (SARA III)

CAS:123-31-9

RTECS #:MX3500000 Fraction by Wt: 5-10% OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: ETHANOLAMINE

CAS:141-43-5

RTECS #:KJ5775000 Fraction by Wt: 5-10% OSHA PEL:3 PPM/6 STEL

ACGIH TLV:3 PPM/6 STEL; 9192

Ingred Name: DIETHANOLAMINE (SARA III)

CAS:111-42-2

RTECS #:KL2975000 Fraction by Wt: 50-55% OSHA PEL:3 PPM

ACGIH TLV:3 PPM; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: AQUEOUS SOLUTION, NON-HAZARDOUS, UNIDENTIFIED COMPONENTS; WT%

BY DIFFERENCE Fraction by Wt: 32.5%

Ingred Name: DIETHANOLAMINE-SULFUR DIOXIDE COMPLEX

CAS:63149-47-3 Fraction by Wt: 1-5%

Other REC Limits: NONE SPECIFIE

D

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: ACUTE: CAUSES SKIN AND EYES

IRRITATION. PROLONGED SKIN CONTACT MAY CAUSE ALLERGIC REACTION.

Effects of

Overexposure:INHALE:IRRITNT;EYES:IRRITNT(VAPORS),BURNS(LIQUID);SKIN:IRRITNT,BURNS,ALLERGIC SKIN REACTION.

First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O*

2 IF NEED:EYES:FLUSH W

LG AMTS H*20 FOR 15 MIN;SKIN:FLUSH W LG AMTS H*20;INGEST:RINSE MOUTH; GET IMMEDIATE MEDICAL ATTENTION FOR EYES OR INGEST.


========= Fire Fighting Measures =============

Flash Point:NONE

Extinguishing Media: SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY PRODUCE DECOMPOSITION PRODUCTS. EXPOSED CONTAINERS MA



Percent Volatiles by Volume:69	
========= Stability and Reactivity Data ===========	
Stability Indicator/Materials to Avoid:YES MINERAL ACIDS Stability Condition to Avoid:EXCESSIVE HEAT	

or:BROWN AQUEOUS MIXTURE;AMMONIA TYPE ODOR.

Hazardous Decomposition Products:SULFUR DIOXIDE

======= Disposal Considerations ===========

Waste Disposal Methods:KEEP IN COVERED CONTAINERS.PENDING
DISPOSAL.HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTER

NATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS. MFG SUGGESTS FLUSH TO SEWER WITH COPIOUS AMOUNTS OF WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.