

KALCOR COATING CO -- V-5708,STAIN,LT REDWOOD,TT-S-708A -- 8010-00-837-7964

=====
Product Identification
=====

Product ID:V-5708,STAIN,LT REDWOOD,TT-S-708A

MSDS Date:01/01/1987

FSC:8010

NIIN:00-837-7964

MSDS Number: BFRXF

=== Responsible Party ===

Company Name:KALCOR COATING CO

Address:37721 STEVENS BLVD

City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

Info Phone Num:216-946-4700

Emergency Phone

Num:216-946-4700

CAGE:33201

=== Contractor Identification ===

Company Name:KALCOR COATING CO

Address:37721 STEVENS BLVD

Box:City:WILLOUGHBY

State:OH

ZIP:44094-6231

Country:US

Phone:216-946-4700

CAGE:33201

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 19.6%

OSHA PEL:100 PPM

Ingred Name:PENTACHLOROPHENOL (SARA III)

CAS:87-86-5

RTECS #:SM6300000

Fraction by Wt: 4.8%

OSHA PEL

:S, 0.5 MG/M3
ACGIH TLV:S, 0.5 MG/M3; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 4.8%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:LINSEED OIL (66.0 MIN % BY WT)
CAS:8001-26-1
RTECS #:OI9690000

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7400000
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

=====
Hazards Identification
=====

Effects of
Overexposure:ACUTE:SKIN & EYE IRRITANT.CHRONIC:INGESTION OF
MATERIAL CAN BE EXTREMELY HARMFUL.

=====
First Aid Measures
=====

First Aid:SKIN & EYE:FLUSH AFFECTED AREA W/PLETY OF WATER FOR 15 MIN.
IF INGESTED, DO NOT INDUCE VOMITING, CALL MD IMMEDIATELY.(ONLY
UNDER MD S DIRECTIONS SHOULD VOMITING BE INDUCED).

=====
Fire Fighting Measures
=====

Flash Point:63F SCC
Extinguishing Media:CO*2, DRY CHEMICAL, FOAM

=

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION, USE DISPOSABLE ABSORBENT. CLEAN AS ANY PAINT.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID EXCESS HEAT, FLAMES & SPARKS

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL VENTILATION NECESSARY

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GOGGLES OR GLASSES

Supplement

al Safety and Health

ADD HAZ INGRED:MAGNESIUM SILICA (TALC)APPROX 14% & PARAFFIN WAX,MIN 2.6% VAPOR DENS:HEAVIER THAN AIR. WT PER GAL>7.95 LBS.DOT:FLAMABLE LIQUID CLASS 1B.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:176-385F

Spec Gravity:0.9600

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:REDDISH LIQUID/PETROLEUM SPIRITS ODOR

Percent Volatiles by Volume:29.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:EXCESS HEAT, SPARKS, OPEN FLAMES

===== Disposal Considerations =====

Waste Disposal Methods:EPA APPROVED INCINERATION OR LANDFILL IF IN ACCORDANCE W/FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The Un

ited States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.