

FARWEST PAINT MFG. CO. -- TT-S-708A LIGHT REDWOOD SEMI-TRANSPARE -- 8010-00-837-7964

=====
Product Identification
=====

Product ID:TT-S-708A LIGHT REDWOOD SEMI-TRANSPARE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-837-7964

MSDS Number: BFRXG

=== Responsible Party ===

Company Name:FARWEST PAINT MFG. CO.

Emergency Phone Num:DAY-206-244-8844

CAGE:DO268

=== Contractor Identification ===

Company Name:FARWES

T PAINT MFR CO

Address:4522 S 133 ST

Box:City:TUKWILLA

State:WA

ZIP:98168

Phone:206-941-1619

CAGE:DO268

Company Name:FEDERAL SPECIFICATIONS, PROMULGATED BY GSA

Box:City:WASHINGTON

State:DC

Country:US

CAGE:81348

=====
Composition/Information on Ingredients
=====

Ingred Name:IRON OXIDES

RTECS #:NO7650000

Fraction by Wt: 6%

Ingred Name:LINSEED OIL PENTA

CAS:8001-26-1

RTECS #:OI9690000

Fraction by Wt: 77%

ACGIH TLV:200PPM

Ingred Name:ALIPHATIC HYDROCARBONS

Fraction by Wt: 16%

A

CGIH TLV:200 PPM

Ingred Name:SUSPENDING AGENT

===== Hazards Identification =====

Effects of Overexposure:EYES-CAN CAUS IRRIT,REDNESS,TEARING.SKIN-PROLNG CONTACT CAN CAUS MODERAT IRRIT,DEFATTING OR DERNATIT

===== First Aid Measures =====

First Aid:SKIN-WASH EXPOS AREA W/SOAP & WATR. EYES-FLUSH W/LG AMT OF WATER-GET MEDICAL ATTN.SWALLOWED-INDUCE VOMITING-CALL AT ONCE DR.BREATHED-REMOV INDIVID TO FRESH AIR.IF B REATHING IS DIFFICULT, ADMINISTER OX YGEN.

===== Fire Fighting Measures =====

Flash Point:104F CC 40C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:ALCOH FOAM,WATR FOG,CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures:SELF-CONTND BREATHING APPARAT W/FUL FACE PIECE.

Unusual Fire/Explosion Hazard:VAPS ARE HEAV THN AIR & MAY TRAVL ALONG THE GROUND OR MOV BY VENTIL OR IGNITED BY PILOT LIGHT,FLAMES

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL-ABSORB LIQUID ON PAPER, VERMICULITE OR OTHER ABSORBENT MATERIAL,LG SPILL-ELIMINATE ALL SOURCES OF IGNITION,STOP SPILL AT SOURCE; DIKE AREA TO PREVENT SPREADING;ABSORB LIQUID W/SAND,CLAY,EA RTH,ABSORBENT & SHOVEL INTO CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN COOL, DRY AREA. DO NOT SMOKE AROUND MATERIAL & DO NOT DROP CONTNRS. HANDLE

WITH CARE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/OSHA JOINTLY APPRVD SELF-CONTND BREATHING APPARATUS.

Ventilation:LOC EXHAUST-SHOULD BE PROVID, MECH-SHOULD BE PROVIDED.

Protective Gloves:NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:313-404

Vapor Density:

4.9

Spec Gravity:.8

Evaporation Rate & Reference:BUAC .13

Solubility in Water:INSOLUBLE

Appearance and Odor:COLORED LIQUID WITH SLIGHT ODOR.

Percent Volatiles by Volume:51.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

===== Disposal Considerations =====

Waste Disposal Methods:SMALL SPILL-ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD.DESTROY REMAINING MATERIAL BY B

URNING IN IRON PAN. LG

SPILL-CONTAMINATED ABSORBENT MAY BE DEPOSITED IN LANDFILL IN ACCORDANCE W/LOC, STATE & FEDERAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should

seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.