

NORRIS PAINT & VARNISH CO,INC. -- INTERIOR,LATEX PAINT -- 8010-00-838-7117

=====  
Product Identification  
=====

Product ID:INTERIOR,LATEX PAINT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-838-7117

MSDS Number: BFRYQ

=== Responsible Party ===

Company Name:NORRIS PAINT & VARNISH CO,INC.

Emergency Phone Num:503-364-2277/8060

CAGE:GO781

=== Contractor Identification ===

Company Name:NORRIS PAINT & VARNISH CO

Box:2023

CAGE:GO781

Company Name:NORRIS PAINT CO., DIV WHITTAKER COATINGS

Address:1675 COMMERCIAL ST NE

Box:2023

City:SALEM

State:OR

ZIP:97308

Country:US

Phone:503-364-2277

CAGE:33148

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PIGMENTS

Fraction by Wt: 38.0%

Ingred Name:VEHICLE

Fraction by Wt: 12.0%

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 2.4%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====  
Hazards Identification  
=====

Effects of Overexposure:INHAL OF VAPORS/SPRAY-SHORTNESS OF BREATH,NAUSEA WHEN INGESTED,VAPOR IRRITATES EYES.

=====  
First Aid Measures  
=====

First Aid:INGESTED:INDUCE VOMIT.CALL DR. EYES: FLUSH WITH WATER FOR 15 MIN. GET DR. INHAL:IF AFFECTED BY VAPOR OR SPRAY MIST REMOVE TO FRESH AIR.

=====  
Fire Fighting Measures  
=====

F  
lash Point:NONE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ABSORB & FLUSH WITH LARGE AMTS. OF WATER IMMEDIATELY.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE UPRIGHT,DO NOT FREEZE.KEEP CONTAINERS CLOSED WHEN NOT IN USE.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:PAINTERS MASK FOR SPRAY APPLICATION  
Ventilation:LOCAL EXHAUST F  
OR OPEN AIR APPLICATION ONLY  
Other Protective Equipment:EYE BATH AND SAFETY SHOWER.  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:N1  
Boiling Pt:B.P. Text:212 F,100 C  
Vapor Pres:24  
Spec Gravity:1.39  
Solubility in Water:COMPLETE  
Appearance and Odor:OPAQUE LIQUID WITH SLIGHT AMMONIA ODOR.  
Percent Volatiles by Volume:65.0

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
OIL & O

ILBASED MATERIALS,PETROLEUM DISTILLATES,STRONG ACIDS

Stability Condition to Avoid:EXTREME HEAT, OVER 200 F

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:FLUSH DOWN DRAIN OR DISPOSE OF IN LANDFILL  
ACCORDING TO LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of Ameri

ca in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.