

DOW CORNING CORP. -- 281 ADHESIVE,DOW CORNING -- 8040-00-843-3460
===== Product Identification =====

Product ID:281 ADHESIVE,DOW CORNING

MSDS Date:09/30/1991

FSC:8040

NIIN:00-843-3460

MSDS Number: BFSGD

=== Responsible Party ===

Company Name:DOW CORNING CORP.

Address:3901 S SAGINAW RD

City:MIDLAND

State:MI

ZIP:48686

Country:US

Info Phone Num:517-496-6000

Emergency Phone Num:517-496-5900

Prepare

r's Name:JACK L. SHENEBERGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 60.0%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 L

BS

===== Hazards Identification =====

Effects of Overexposure:SKIN & EYE IRRITANT. MAY CAUSE SLIGHT ANESTHESIA, HEADACHES, ETC.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN & EYES: FLUSH WITH WATER. OBTAIN MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:64F,18C

Extinguishing Media:CO*2 OR FOAM, DRY CHEMIC AL, WATERFOG.

Fire Fighting Procedures:NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE CLOTHING SHOULD BE WORN IF FIGHTING FIRES INVOLVING CHEMICALS.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND CAN TRAVEL ALONG GROUND TO REMOTE IGNITION SOURCES.

===== Accidental Release Measures =====

Spill Release Procedures:MOP, WIPE OR SOAK UP WITH ABSORBENT MATERIAL USING PROPER PROTECTIVE EQUIPMENT.

===== Handling and Storage =====

=====

Handling and Storage Precautions:SAME AS FOR ANY FLAMMABLE PRODUCT. USE REASONABLE CARE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC VAPOR TYPE

Ventilation:MECHANICAL VENTILATION RECOMMENDED

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS REQUIRED BY LOCAL POLICY.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Tex

t:290F,143C

Vapor Pres:25

Vapor Density:3.7

Spec Gravity:0.94

Evaporation Rate & Reference: