

PRATT & LAMBERT-WICHITA DIV. -- 745-702 -- 8010-00-844-4792

=====  
Product Identification  
=====

Product ID:745-702

MSDS Date:01/01/1985

FSC:8010

NIIN:00-844-4792

MSDS Number: BFSHY

=== Responsible Party ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Emergency Phone Num:316-733-1361

CAGE:KO010

=== Contractor Identification ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Box:2153

CAGE:KO010

Company Nam

e:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 45.0%

OSHA PEL:100 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:INHAL:ANESTHETIC & IRRITATION TO  
AIRWAY;IRRITATION-SKIN/EYE CONTACT;HEADACHE,DIZZY,COMA

=====

=====  
First Aid Measures  
=====

First Aid:FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING  
CONTAMINATED CLOTHING.INHAL:REMOVE TO FRESH AIR.CALL MD. IF  
SYMPTOMS PERSIST.

=====  
Fire Fighting Measures  
=====

Flash Point:104 F, 40 C, TCC

Lower Limits:1.1

Extinguishing Media:CARBON DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE  
FIRE

Fire Fighting Procedures:SELF-CONTANED BREATHING APPARATUS AVAILABLE  
FOR FIREMEN

Unusu

al Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE DUE TO PRESSURE BUILD-UP

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF  
IGNITION(FIRE,SPARKS...). AVOID BREATHING VAPORS.VENTILATE AREA.  
REMOVE WITH INERT ABSORBENT AND NON SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE  
AMTS IN BUILDIN

GS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS  
ONE FLAMMABLE (OR COMBUSTIBLE)LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED  
WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME  
CUT,BRAZE,OR WELD COATED MATERIAL W/O VENTILATION.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER  
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV  
&LEL SAFETY &  
WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING.

Supplemental Safety and Health

BOILING RANGE 155-189 C.

=====  
Physical/Chemical Properties  
=====

Boiling Pt:B.P. Text:311-373 F

Evaporation Rate & Reference:< ETHER

Appearance and Odor:BLACK PAINT.

Percent Volatiles by Volume:59.0

=====  
Stability and Reactivity D

ata =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: FIRES, HEAT & HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IAW LOCAL, STATE, AND FED. REGULATIONS.  
INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED  
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.