

KOPPERS CO, INC. -- A-913A -- 8010-00-848-9272

=====
Product Identification
=====

Product ID:A-913A
MSDS Date:01/01/1985
FSC:8010
NIIN:00-848-9272
MSDS Number: BFSLX
=== Responsible Party ===
Company Name:KOPPERS CO, INC.
Emergency Phone Num:213-726-8666
CAGE:EO546
=== Contractor Identification ===
Company Name:KOPPERS CO INC
Address:5431 DISTRICT BLVD
Box:City:VERNON
State:CA
ZIP:90040
Country:U
S
CAGE:71191
Company Name:KOPPERS CO, INC.
CAGE:EO546

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ALIPHATIC HYDROCARBONS
ACGIH TLV:130 PPM

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rp

t Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:VAPORS - 50PPM IRRITATE EYES,NOSE&THROAT.
HIGHER CONC-DROWSINESS,DIZZINESS FOLLOWED BY COMA.

=====
===== First Aid Measures =====

First Aid:VAPORS-REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTICIAL

RESPIRATION. CALL DOCTOR. SKIN-WASH THOROUGHLY W SOAP & WATER.
EYES-FLUSH W LGE AMTS WATER FOR 15 MIN.-GET MEDICAL AID.
INGESTION-DO NOT INDUCE VOMITING.CALL DOCTOR IMMEDIATELY.

=====
===== Fire Fighting Measures =====

Flash Point:25F, -4C TCC

Extinguishing Media:WATER, FOG, DRY CHEM OR CO2

Fire Fighting Procedures:AIR SUPPLIED EQUIP/ENCLOSED AREA. COOL FULL
CONTAINERS/WATER

Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT, SPARK OR OPEN FLAME

=

=====
===== Accidental Release Measures =====

Spill Release Procedures:RECOVER ALL POSSIBLE, THEN WIPE UP W RAGS,
SAWDUST, ETC. REMOVE ALL SOURCES OF IGNITION.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. AVOID FLAMES,
WELDING, SMOKING,SPARKS, OPEN LIGHTS, ETC.

Other Precautions:0001MAINTAIN GOOD PERSONAL HYGIENE. DO NOT USE IN
CONFINED AREAS, TANK OR PIT WO ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL & MECHANICAL
Protective Gloves:RUBBER
Eye Protection:GOGGLES
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Density:>AIR
Evaporation Rate & Reference:MODERATE
Solubility in Water:SLIGHT
Appearance and Odor:TYPICAL PAINT ODOR
Percent Volatiles by Volume:63.2

===== Stability and Reactivity Data =====

Stability Indicator/
Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORD W LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.