

FISKE BROTHERS REFINING CO. -- LUBRIPLATE 130-AA -- 9150-00-857-9079

=====
Product Identification
=====

Product ID:LUBRIPLATE 130-AA

MSDS Date:01/01/1987

FSC:9150

NIIN:00-857-9079

MSDS Number: BFTBM

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO.

Emergency Phone Num:419-691-2491

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OA

KDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM SOAP

Ingred Name:MINERAL OIL

Ingred Name:ADDITIVES

=====
Hazards Identification
=====

Effects of Overexposure:SKIN,EYE IRRITATION.

=====
First Aid Measures
=====

First Aid:EYE:FLUSH WITH CLEAR WATER FOR 15MIN OR TILL IRRITATION
SUBSIDES,IF I

IRRITATION PERSISTS. CONSULT PHYSICIAN; SKIN: REMOVE ANY
CONTAMINATED CLOTHING & WASH THOROUGHLY WITH SOAP & WARM WATER.

===== Fire Fighting Measures =====

Flash Point: 400F/204C(COC)

Lower Limits: 1

Upper Limits: 7

Extinguishing Media: SM: CO*2, DRY CHEM. LG: H*2O SPRAY, FOG OR FOAM

Fire Fighting Procedures: WEAR SELF-CNTD BRTHG, APP H*2O SPRAY TO COOL
CONTR.

Unusual Fire/Explosion Hazard: EMPTY CONTAINERS ETAIN RESIDUE. DO NOT
CUT, DRILL, GRIND OR WELD AS THEY MA
Y EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures: SCRAPE UP GREASE, WATER REMAINDER WITH SUITABLE
PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF
SEWERS & WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR
MAY ENTER SEWERS & WATER COURSES.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, DRY WELL VENTED, LOW FIRE
RISK AREA. PROTECT FR
HEAT, SHOCK KEEP CONTAINERS CLOSED.

Other Precautions: AVOID BREATHING OIL MIST. REMOVE OIL-SOAKED CLOTHING
AND LAUNDRER BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NONE

Ventilation: LOCAL EXHAUST.

Protective Gloves: OIL-RESIST.

Eye Protection: CHEM SPLASH GOGGLES

Other Protective Equipment: OIL-RESISTANT APRON.

Supplemental Safety and Health

MSDS DATED 11-85.

===== Physical/Chemical Properties =====

HCC: V

6

Boiling Pt:B.P. Text:>550F/288C

Vapor Pres:NIL

Vapor Density:>5

Spec Gravity:0.95

Evaporation Rate & Reference: