

ESSEX CHEMICAL CORP PRO-SEAL DIV -- PRO SEAL 870 -- 8030-00-871-8489

===== Product Identification =====

Product ID:PRO SEAL 870  
MSDS Date:01/01/1985  
FSC:8030  
NIIN:00-871-8489  
Kit Part:Y  
MSDS Number: BFTJD  
=== Responsible Party ===  
Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV  
Address:19451 SUSANA RD  
City:COMPTON  
State:CA  
ZIP:90221-5713  
Country:US  
Info Phone Num:310-537-7600  
Emergency Phone Num:31  
0-537-7600  
CAGE:83527  
=== Contractor Identification ===  
Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV  
Address:19451 SUSANA RD  
Box:City:COMPTON  
State:CA  
ZIP:90221-5713  
Country:US  
Phone:310-537-7600  
CAGE:83527

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 25%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

===== Hazards Identification

=====

Effects of Overexposure:MAY CAUSE SKIN OR EYE IRRITATION

===== First Aid Measures =====

First Aid:WASH AFFECTED AREA COPIOUSLY WATH WATER. GIVE EMETIC IF  
INGESTED CONSULT PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:40F.5C  
Lower Limits:1.3  
Upper Limits:6.8  
Extinguishing Media:CO2, FOAM, DRY CHEMICAL  
Fire Fighting Procedures:WATER NOT RECOMMENDED  
Unusual Fire/Explosion Hazard:VOLAT  
ICE SOLVENT

===== Accidental Release Measures =====

Spill Release Procedures:WIPE WITH RAGS OR SOLVENT

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT INGEST. WASH HANDS THOROUGHLY  
AFTER HANDLING, STORE BELOW 80F  
Other Precautions:AVOID SPARKS AND OPEN FLAMES RED LABEL FLAMMABLE  
MATERIAL

===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL-STRONG POSITIVE AI  
RFLOW  
Protective Gloves:RECOMMENDED  
Eye Protection:RECOMMENDED  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2  
Boiling Pt:B.P. Text:230F.110C  
Vapor Pres:38  
Vapor Density:3.1  
Spec Gravity:1.25  
Evaporation Rate & Reference:1.9 BUAC=1  
Percent Volatiles by Volume:35

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
CO, CO2, SO2, HCHO UPON COMBUSTION.

=====

Disposal Considerations =====

Waste Disposal Methods: NORMAL METHODS, BUT PREFERABLY BY BURNING

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.