View NSN Online: https://aerobasegroup.de/nsn/8010-00-900-2938

## CORONADO PAINT COMPANY, INC -- PAINT, TRAFFIC, WHITE -- 8010-00-900-2938

Product ID:PAINT, TRAFFIC, WHITE

MSDS Date:01/01/1987

FSC:8010

NIIN:00-900-2938

MSDS Number: BFVKD === Responsible Party ===

Company Name: CORONADO PAINT COMPANY, INC

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812 Country:US CAGE:33200

=== Contractor Identification =

==

Company Name: CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812 Country:US

Phone:904-428-6461

CAGE:33200

======= Composition/Information on Ingredients ========

Ingred Name: ALIPHATIC AND AROMATIC HYDROCARBONS

Fraction by Wt: 16.3% ACGIH TLV:100 PPM

Ingred Name:PIGMENTS Fraction by Wt: 50.4% ACGIH TLV:NO HAZARD

Ingred Name: VINYL TOLUENE BUTADIENE

Fraction by Wt: 16.3% ACGIH TLV:NO HAZARD

====== Hazards Identific

| Effects of Overexposure:SEVERE EYE IRRITATION. DRY SKIN. INHALATION-HEADACHE, DIZZINESS, AND NAUSEA.  |
|---|
| ======================================  |
| First Aid:EYE CONTACT-FLUSH WITH WATER. SKIN CONTACT-WASH WITH MILD SOAP AND WATER; APPLY SKIN CREAM. INHALATION-REMOVE TO FRESH AIR AND CALL A PHYSICIAN; APPLY ARTIFICIAL RESPIRATION, IF NECESSARY.  |
| ========== Fire Fighting Measures ============  |
| Flash Point:53 F ;12 C. SCC Lower Limits:0.9 Upper Limits:7.0 Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:TREAT AS CLASS B FIRE. Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR. |
| ======== Accidental Release Measures =========  |
| Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO RETAING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE, OR HOT METAL SURFACES.   |
| ======================================  |
| Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.   |
| ====== Exposure Controls/Personal Protection =======  |
| Respiratory Protection:SELF CONTAINED NIOSH APPROVED PROTECTION IF TLV IS EXCEEDED.  Ventilation:LOCAL-YES Protective Gloves:YES Eye Protection:YES Other Protective Equipment:EYE BATH AND SAFETY SHOWER. Supplemental Safety and Health       |
| ====  |

ation ========

| ======= Physical/Chemical Properties ==========   |
|---|
| HCC:F3 Boiling Pt:B.P. Text:133 F,56 C Vapor Pres:6 Vapor Density:3.7 Spec Gravity:1.32 Evaporation Rate & DIAC Solubility in Water:SLIGHT Appearance and Odor:WHITE OPAQUE LIQUID, PETROLEUM DISTILLATE ODOR. Percent Volatiles by Volume:58.5 |
| ========= Stability and Reactivity Data =========   |
| Stability Indicator/Materials to Avoid:YES<br>STRONG OXIDIZING AGENTS.<br>Stability Condition to Avoid:HEAT, SPAR<br>KS, OPEN FLAME OR FIRE.<br>Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON<br>MONOXIDE.            |
| ======== Disposal Considerations ===========  |
| Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE AND SUPERVISED CONDITIONS.   |
| Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department   |

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.