

NORRIS PAINT CO., DIV WHITTAKER COATINGS -- TT-P-115E TYPEIII -- 8010-00-900-3650

=====
Product Identification
=====

Product ID:TT-P-115E TYPEIII

MSDS Date:01/01/1987

FSC:8010

NIIN:00-900-3650

MSDS Number: BFVLB

=== Responsible Party ===

Company Name:NORRIS PAINT CO., DIV WHITTAKER COATINGS

Address:1675 COMMERCIAL ST NE

Box:2023

City:SALEM

State:OR

ZIP:97308

Country:US

Info Phone Num:503-364-2277

Emergency Phone Num:503-364-2277

CAGE:33148

=== Contractor Identification ===

Company Name:NORRIS PAINT CO., DIV WHITTAKER COATINGS

Address:1675 COMMERCIAL ST NE

Box:2023

City:SALEM

State:OR

ZIP:97308

Country:US

Phone:503-364-2277

CAGE:33148

=====
Composition/Information on Ingredients
=====

Ingred Name:PIGMENTS

Fraction by Wt: 59%

ACGIH TLV:50MG/M3/8 HR

Ingred Name:VEHICLE

Fraction by Wt: 16.5%

Ingred Name:SOLVENTS

Fraction by Wt: 22.5%

ACGIH TLV:200 PPM

Ingred Name:ADDI

TIVE
Fraction by Wt: 2.0%

===== Hazards Identification =====

Effects of Overexposure: INHAL OF HIGH CONCENTRATIONS AT MEST MAY LEAD TO ASPHYIATION POSSIBLE CENTRAL NERVOUS SYSTEM.

===== First Aid Measures =====

First Aid: IF SWALLOWED GET DR. DO NO INDUCE VOMIT. REMOVE TO FRESH AIR. FOR EYE CONTACT FLUSH EYES WITH LARGE AMTS OF WATER.

===== Fire Fighting Measures =====

Flash Poin

t: 16 F TCC

Lower Limits: 1

Upper Limits: 7

Extinguishing Media: DRY CHEM. OR ALCHOHL TYPE FOAM

Fire Fighting Procedures: USE WATER SPRAY TO COOL FIRE EXPOSED SURFACE

Unusual Fire/Explosion Hazard: TOXIC FUMES MAYBE LIBERATED RESPIRATORY PROTECTION RE-QUIRED FOR FIRE FIGHTING PERSONNEL

===== Accidental Release Measures =====

Spill Release Procedures: CONTAIN SPILL WITH SAND EARTH ETC. DO NOT ALLOW MATERIAL TO ENTER SEWER, WATER COURSES OR LOW AREAS.

=====

===== Handling and Storage =====

Handling and Storage Precautions: STORE CONTAINER UPRIGHT. KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT USE NEAR HEAT FLAME OR STRONG OXIDANTS. ADEQUATE VENTILATION NEEDED.

Other Precautions: ALL HANDLING EQUIP. SHOULD BE GROUNDED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: SELF CONTAINED BREATHING APPARATUS IF ABOVE TLV LIMIT VALUE.

Ventilation: 60+BM IN CONFINED SPACE VENTILATIN EQUIP.

Protective Gloves:CHEM.RESIST
Eye Protection:GOGGLES
Other Protective Equipment:EYE BATH AND SAFETY SHOWER.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:175-79.4
Vapor Pres:70
Vapor Density:4.5
Spec Gravity:1.47
Evaporation Rate & Reference:2
Solubility in Water:INSOL
Appearance and Odor:YELLOW OPAQUE LIQUID STRONG SOLVENT ODOR.
Percent Volatiles by Volume:41

===== Stability and Reactivity Data

=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:TEMP.ABOVE 120 F SPARKS OPEN FLAME
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CO*2.

===== Disposal Considerations =====

Waste Disposal Methods:COLLECT ABSORBED SPILLAGE,DILUTE WITH
WATER.DISPOSE OF IN LANDFILL ACCORDING TO LOCAL REGULATIONS. DO NOT
INCINERATE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.