

PRATT AND LAMBERT INC -- 745614 ENAMEL ALKYD SG GRAY 26152 -- 8010-00-901-1059

=====
Product Identification
=====

Product ID:745614 ENAMEL ALKYD SG GRAY 26152

MSDS Date:01/01/1985

FSC:8010

NIIN:00-901-1059

MSDS Number: BFVMN

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency

Phone Num:316-733-1361

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 35%

ACGIH TLV:500 PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;919

2
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:VOC. ORGANIC CMPD 3.7 LB/GAL LESS WATER & NPRS* 444 G/L
LESS WATER VOC. 8.4 LB/GAL SOLIDS 1008 G/L SOLIDS CALCU
RTECS #:9999999VO

=====
===== Hazards Identification =====

Effects of Overexposure:INHALATION-ANESTHETIC,IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

=====
===== First Aid Measures =====

First Aid:CONTACT-FLUSH SKIN AND EYES WITH WATER WHILE REMOVING CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. CALL PHYSICIAN IF SYMPTOMS PERSIST.

=====
===== Fire Fighting Measures =====

Flash Point:104F, 40C TCC
Lower Limits:1.10
Extinguishing Media:NFPA CLASS B EXTINGUISHER; POLYMER FOAM FOR LARGE FIRES
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTI

LATE AREA. REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F STORE LARGE
QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106
Other Precautions:GROUND CONTAINERS WHEN POURING.AVOID FREE FALL OF
LIQUID IN XS OF FEW INCHES DO NOT FLAME CUT, BRAZE OR WELD COATER
MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPRIATE
VENTILATION

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:OPEN AREA:BUR MINES MECH RESPIRATOR;CLOSED:BUR
MINES CHEM/MECH FILTE
Ventilation:GENERAL DILUTION OF LOCAL EXHAUST TO KEEP TLV BELOW LIMIT
Protective Gloves:REG IF LONG CON
Eye Protection:TO PROTECT VS SPLASHING
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING.
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F2
B
Boiling Pt:B.P. Text:311-373F
Vapor Density:ETHER
Percent Volatiles by Volume:57

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS-INCINERATE IN APPROVED FACILITY-DO NOT
INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.