

DETROIT BODY FILLER INC. -- FILLER, DENT -- 8010-00-926-2135

=====
Product Identification
=====

Product ID:FILLER, DENT
MSDS Date:05/01/1987
FSC:8010
NIIN:00-926-2135
Kit Part:Y
MSDS Number: BFWTT
=== Responsible Party ===
Company Name:DETROIT BODY FILLER INC.
Address:4700 - 13TH STREET
City:WYANDOTTE
State:MI
ZIP:48192
Country:US
Info Phone Num:313-285-1480
Emergency Phone Num:313-285-1480
CAGE:
DETRO
=== Contractor Identification ===
Company Name:DETROIT BODY FILLER INC.
Address:4700 - 13TH STREET
Box:City:WYANDOTTE
State:MI
ZIP:48192
Country:US
Phone:313-285-1480
CAGE:DETRO

=====
Composition/Information on Ingredients
=====

Ingred Name:STYRENE, MONOMER (SARA III)
CAS:100-42-5
RTECS #:WL3675000
Fraction by Wt: 13-18%
OSHA PEL:100 PPM
ACGIH TLV:S,50PPM/100STEL;9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:CAUSES SKIN AND EYE IRRITATION. MAY CAUSE DROWSINESS. IF INGESTED CAN CAUSE NAUSEA, GASTROINTESTINAL IRRITATION, VOMITING, DIARRHEA. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS.PROLONGED INHALATION OF VAPORS MAY CAUSE LUNG DAMAGE.

Effects of Overexposure:NONE
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

F
First Aid:EYES-IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. SEE A PHYSICIAN. SKIN-WASH THOROUGHLY WITH SOAP AND WATER. INHALATION-REMOVE TO FRESH AIR.INGESTION-DO NOT INDUCE VOMITING. SEE A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:89-90F - 32C
Extinguishing Media:FOAM, CARBON DIOXIDE OR DRY CHEMICALS
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF SMOKE
Unusual Fire/Explosion Hazard:NONE KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSING.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID TEMPERATURES OF OVER 100F IN STORAGE.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Resp

iratory Protection:100 PPM AND ABOVE, USE SELF CONTAINER APPARATUS
(FOR STYRENE).

Ventilation:LOCAL EXHAUST SHOULD BE SUFFICIENT. MECHANICAL (GENERAL)
VENTILATION COULD BE USEFUL.

Protective Gloves:NONE NEEDED

Eye Protection:WEAR GOGGLES

Other Protective Equipment:NONE NEEDED

Work Hygienic Practices:NORMAL WORK CLOTHES

Supplemental Safety and Health

PART "A" OF TWO PART PRODUCT. SEE P/N INDICATOR B FOR PART "B".

===== Physical/Chemical Properties =====

Vapor

Density:3.6

Spec Gravity:1.6-1.8

Evaporation Rate & Reference: