View NSN Online: https://aerobasegroup.de/nsn/6850-00-926-8960 OCTAGON PROCESS, INC -- MIL-B-24155B(SH)BOILER SCALE REMVG CMPD -- 6850-00-926-8960 Product ID:MIL-B-24155B(SH)BOILER SCALE REMVG CMPD MSDS Date:01/27/1989 FSC:6850 NIIN:00-926-8960 MSDS Number: BFWXJ === Responsible Party === Company Name: OCTAGON PROCESS, INC Address:596 RIVER ROAD

City:EDGEWATER

State:NJ ZIP:07020 Country:US

Info Phone Num:201-945-9400

Emergenc

y Phone Num:201-945-9400

CAGE:DO973

=== Contractor Identification ===

Company Name: OCTAGON PROCESS INC.

Address:596 RIVER ROAD Box:City:EDGEWATER

State:NJ ZIP:07020 Country:US

Phone:201-945-9400

CAGE:82925

Company Name: OCTAGON PROCESS, INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Phone:201-945-9400

CAGE:DO973

======= Composition/Information on Ingredients ========

Ingred Name: SULFAMIC ACID

CAS:5329-14-6

RTECS #:WO5950000

====== Haza

rds Identification ===========
Health Hazards Acute and Chronic:ACUTE:EYES AND SKIN BURNS,DAMAGE TO RESPIRATORY TRACT OR MUCOUS MEMBRANES;COUGHING,SNEEZING. CHRONIC:RESPIRATORY DISEASE;DERMATITIS. Effects of Overexposure:SEE HEALTH HAZARDS DATA. Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN.
======================================
First Aid:WASH AFFECTED AREAS OF SKIN WITH SOAP & WATER. FLUSH EYES WITH PLENTY OF WATER.
======================================
Flash Point:NONE Extinguishing Media:USE SUITABLE MEDIA FOR SURROUNDING FIRE. Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA. Unusual Fire/Explosion Hazard:EMITS TOXIC FUMES OF SULFUR OXIDES WHEN HEATED TO DECOMPOSITION.
======== Accidental Release Measures =========
Spill Release Procedures:SWEEP UP WITH SODA ASH, PUT INTO CARTONS & INCINERATE
======================================
Handling and Storage Precautions:STORE IN COOL, DRY PLACE AWAY FROM OXIDIZERS
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR MIST OR DUST IF ABOVE TLV/PEL. Ventilation:GENERAL/MECHANICAL TO MAINTAIN TLV/PEL.

Protective Gloves: RUBBER/NEOPRENE Eye Protection:GOGGLES/FACE SHIELD
Other Protective Equipment:RUBBER APRON
Work Hygienic Practices:AVOID

VAPORS/MIST.
Supplemental Safety and Health
======== Physical/Chemical Properties ==========
HCC:C1
Decomp Temp:Decomp Text:410F
Vapor Density:2.03
Solubility in Water:COMPLETE
Appearance and Odor:WHITE TO OFF WHITE CRYSTALLINE SOLID,SLIGHT ACIDIC ODOR
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES
CHLORINE, NITRIC ACID, STRONG OXIDIZERS
Stability Condition t
o Avoid:EXTREME HEAT
Hazardous Decomposition Products:OXIDES OF NITROGEN OR SULFUR.
======= Disposal Considerations ==========

CONTACT WITH EYES AND SKIN; DO NOT BREATHE

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.