View NSN Online: https://aerobasegroup.com/nsn/9150-00-953-1694

Product ID:LUBRIPLATE 930-AA MSDS Date:06/01/1987 FSC:9150 NIIN:00-953-1694 **MSDS Number: BFYYX** === Responsible Party === Company Name: FISKE BROS REFINING CO Address:129 LOCKWOOD ST **City:NEWARK** State:NJ ZIP:07105-4720 Country:US Info Phone Num:201-589-9150 Emergency Phone Num:201-589-9150 Preparer's Name: ROBERT J. SIBILIA CAGE:73219 === Contractor Identification === Company Name: FISKE BROS REFINING CO Address:129 LOCKWOOD ST Box:City:NEWARK State:NJ ZIP:07105-4720 Country:US Phone:201-589-9150 CAGE:73219 Company Name: INDUSTRIAL SUPPLY CORP Address:1905 WESTWOOD AVE Box:6356 City:RICHMOND State:VA ZIP:23230 Country:US Phone:804-355-8041 CAGE:6A908

Ingred Name:MINERAL OIL(NOT SPECIFIED) OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3 Ingred Name: INORGANIC THICKENER

Ingred Name:ADDITIVES CAS:24937-78-8

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: EYE: MAY BE MILDLY IRRITATING. SKIN: RELEASE DURING HIGH PRESSURE USAGE MAY RESULT IN INJECTION OF OIL INTO THE SKIN CAUSING LOCAL NECROSIS. INHALATION:NOT EXPECTED TO BE A RELEVANT ROUTE OF EXP OSURE ; HIGH TEMPERATURE VAPORS IRRITATERESPIRATORY TRACT. Explanation of Carcinogenicity:DATA PER MSDS Effects of Overexposure: EYES: MAY CAUSE TEMPORARY DISCOMFORT WITH MILD REDNESS AND DRYNESS SIMILAR TO WINDBURN; SKIN: SEVERAL REPEATED PROLONGED EXPOSURES MAY CAUSE IRRITATION. INHALATION: NO INJURY IS LIKELY FROM RELATIVELY SHORT EXPOSURE OF LESS THAN 8 HOURS. INGESTION: SWALLOWING LARGE AMOUNTS MAY CAUSE DIGESTIVE DISCOMFORT. Medical Cond Aggravated by Exposure: PRE-EXISTING SKIN **DISORDERS MAY BE** AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION. EYE: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: WASH WITH S OAP & WATER/WATERLESS CLEANER. REMOVE CONTAMINATED CLOTHING. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOM ITING. IN GENERAL, NO TREATMENT IS REQUIRED. GET MEDICAL ADVICE.

Flash Point Method:COC
Flash Point:400F,204C
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual F

ire/Explosion Hazard:DONOT STORE/MIX W/STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE; DONOT CUT, DRILL,/WELD!!

CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES (SHOES) THAT CAN NOT BE DECONTAMINATED.

Respiratory Protection:NORMALLY NOT NEEDED.USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/,MIST AS REQUIRED IF ABOVE PEL/TLV. Ventilation:NORMAL ROOM VENTILATION

Protective Gloves: NEOPRENE RUBBER AS REQUIRED.

Eye Protection: SAFETY GLASSES RECOMMENDED.

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOM

MENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

MANUFACTURER SUPPLIED MSDS FOR 930 SERIES OF HIS PRODUCTS(GREASES) WHICH INCLUDES 930-A, 930-2, 930-AA, 930-AAA.

HCC:V6

NRC/State Lic Num:NONE Boiling Pt:B.P. Text:>550F/>288C Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID Vapor Pres:5. Spec Gravity:0.94-0.97 Evaporation Rate & amp; Reference: