

FILTRON CO INC -- FA5121 -- 5915-00-959-4379

=====  
===== Product Identification =====

Product ID:FA5121  
MSDS Date:01/01/1985  
FSC:5915  
NIIN:00-959-4379  
MSDS Number: BFZGG  
=== Responsible Party ===  
Company Name:FILTRON CO INC  
Address:148 SWEET HOLLOW RD  
City:OLD BETHPAGE  
State:NY  
ZIP:11804-1315  
Country:US  
Emergency Phone Num:914-699-2000  
CAGE:81831

==== Contractor Identification ====

Company Name:FILTRON CO  
INC  
Address:148 SWEET HOLLOW RD  
Box:City:OLD BETHPAGE  
State:NY  
ZIP:11804-1315  
Country:US  
Phone:914-699-2000  
CAGE:81831

=====  
===== Composition/Information on Ingredients =====

Ingred Name:POLYCHLORINATED BIPHENYLS (PCBS) (SARA III)  
CAS:1336-36-3  
RTECS #:TQ1350000  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

=====  
===== Hazards Identification =====

Effects of Overexposure:INHAL:RESP TK IRRIT;  
SKIN/EYE;IRRIT,INFLAM,CHLORACNE; MAY CAUSE LIVER DAMAGE

=====

===== First Aid Measures =====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG, GIVE CPR. IF BRTHNG DIFF, GIVE OXYGEN. EYES:IMMED FLUSH W/PLENTHY OF WATER. SKIN:WASH W/SOAP&WATER.RMV CONTAM CLTHNG&SHOES.INGEST:INDUCE VOMIT.RPT UNTIL VOMIT IS CLEAR.NOTHNG BY MOUTH IF UNCONSC.GET MEDICAL ATTN.

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:EXTINGUISH W. AGENT SUITABLE FOR SURROUNDING FIRE.  
Fire F  
ighting Procedures:WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD BRTHG APP.  
Unusual Fire/Explosion Hazard:MATL IS NON-FLAMMABLE BUT MAY GENERATE TOXIC FUMES IN HEAT OF FIRE

===== Accidental Release Measures =====

Spill Release Procedures:EVAC NON-ESSENTL PERSONNEL. VENT SPIL AREA. WEAR PROTECT EQUIPT. STOP LEAK. SOAK UP LIQUID W/NON-REACTIVE MATL (SAND, DIRT, ETC) OR RMV BY DIKE & PUMPING OR OTHER SUITABLE MEANS. CLEAN AREA W/SUITABLE SAFETY SOL VENT. LAUNDER CONTAMINATED CLOTHING.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED  
Other Precautions:CHLORODIPHENYLS MAY ATTACK SOME TYPES OF RUBBER AND PLASTIC. DO NOT USE CONTAMNINATED WORK CLOTHING. WASH/SHOWER AFTER EXPOSURE TO PCB'S.

===== Exposure Controls/Personal Protection =

=====

Respiratory Protection:NIOSH/MESA APPR SCBA/AIR SUPP RESPIR.  
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.  
Protective Gloves:IMPERVIOUS  
Eye Protection:GOGGLES/FACE SHIELD  
Other Protective Equipment:WEAR FULL PROTECTIVE CLOTHING.  
Supplemental Safety and Health  
OVEREXPOS:CAN CAUSE FORMATION OF CYSTS.CAUSES STILLBIRTHS.IRRITATES EYES,NOSE,THROAT.

===== Physical/Chemical Properties =====

HCC:Z3  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:PALE Y

ELLOW VISCOUS LIQUID W/HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: SEE OTHER PRECAUTIONS

Hazardous Decomposition Products: HYDROGEN CHLORIDE, CO, & OTHER  
TOXIC/IRRITATING GASES/FUMES

===== Disposal Considerations =====

Waste Disposal Methods: CONTROLLED DISPOSAL RQD. GEN. V. HIGH TEMP  
INCINERATION. IAW ALL LOCAL, STATE,  
& FEDERAL REGULATIONS.  
PERMITTED DISPOSAL OPERATOR REQUIRED.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for  
or the suitability of this information to their  
particular situation.