View NSN Online: https://aerobasegroup.de/nsn/5640-00-960-2496

Product ID:TRANSITE, FLAT MSDS Date:04/09/1985 FSC:5640 NIIN:00-960-2496 MSDS Number: BFZGP === Responsible Party === Company Name: MANVILLE SALES CORP. Box:5108 City:DENVER State:CO ZIP:80217-5108 Info Phone Num:303-978-2000 Emergency Phone Num:303-978-3120 CAGE:75165 === Contractor Identification === Com pany Name:SCHULLER INTERNATIONAL INC. Box:5108 City:DENVER State:CO ZIP:80217-5108 Country:US Phone:303-978-4900 CAGE:75165

Ingred Name:ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE 29CFR 1910.1101) CAS:1332-21-4 RTECS #:CI6475000 Fraction by Wt: 40% OSHA PEL:0.2 FIBERS/CC ACGIH TLV:0.5 FIBERS/CC; A1;89 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name:PORTLAND CEMENT

CAS:65997-15-1 RTECS #:VV8770000 Fraction by Wt: 60% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic: EXCESSIVE EXPOSURE TO HIGH CONCENTRATIONS OF AIRBORNE ASBESTOS FIBERS CAN CAUSE CHRONIC PULMONARY DISEASE. THERE ARE NO ACUTE SIGNS OR SYMPTOMS ASSOCIATED WITH ASBESTO. THE DISEASE ASSOCIATED WITH OVE REXPOS **URE ARE** CHRONIC, GENERALLY TAKINGFROM 10 TO 40 YEARS TO BECOME APPARENT. Explanation of Carcinogenicity: CONSIDERED A KNOWN HUMAN CARCINOGEN. Effects of Overexposure: EXCESSIVE EXPOSURE TO HIGH CONCENTRATION OF AIRBORNE ASBESTOS FIBER CAN CAUSE CHRONIC PULMONARY DISEASE AND CANCER. FIBERS CAN BECOME IMBEDDED IN SKIN AND IN SOME CASES RESULT IN ASBESTOS "CORNS". CUR RENT STUDIES ESTABLISH NO RELATION OF ASBESTOS FIBERS AS FOUND IN ENVIRONMENT. Medical Cond Aggravated by Exposure :PRE-EXISTING UPPER RESPIRATORY AND

LUNG DISEASE SUCH AS BUT NOT LIMITED TO BRONCHITIS, EMPHYSEMA AND ASTHMA.

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN CONTACT: WASH OR SHOWER THOROUGHLY USING SOAP AND WARM WATER. EYES: FLUSH WITH COPIOUS QUANTITIES OF WATER.

Flash Point:NONE Autoignition Temp:Autoignition Temp Text:NONE Extinguishing Media:NOT REQUIRED Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: VACUUM CLEAN SPILLAGE AND DUST CREATED DURING FABRICATION. IF SWEEPING IS NECESSARY, WET DOWN SPILLAGE. USE RESPIRATORY PROTECTION AS REQUIRED. Neutralizing Agent: NONE

Handling and Storage Precautions:STORE FLAT Other Precautions:SMOKING GREA TELY INCREASES THE CHANGE FOR ASBESTOS-RELATED LUNG DISEASE. IF YOU WORK WITH ASBESTOS DO NOT SMOKE. Respiratory Protection: USE NIOSH APPROVED RESPIRATOR SUCH AS 3M MODEL 9900 OR EQUIALENT FOR PROTECTION AGAINST PNEUMOCONIOSIS PRODUCING DUST. Ventilation: CONTROL WITH MECHANICAL DUST COLLECTION EQUIPMENT TO WITHIN TLV. Protective Gloves:NOT NORMALLY REQUIRED Eye Protection: GOGGLES RECOMMENDED WHEN USING POWE RTOOL Other Protective Equipment: USE SPECIAL CLOTHING AS REQUIRED BY OSHA STANDARD FOR EXPOSURE TO ASBESTOS DUST 29 CFR 1910.1001(D). Work Hygienic Practices: USE ALL PROPER PROTECTIVE EQUIPMENT WHEN POSSIBILITY OF EXPOSURE TO ASBESTOS DUSTS EXISTS. Supplemental Safety and Health NONE HCC:T7 Spec Gravity:1.6 Solubility in Water:NEGLIGIBLE Appearance and Odor: GRAY SOLID SHEET - NO ODOR Percent Volatiles by Volume:0 === Stability Indicator/Materials to Avoid:YES NO KNOWN INCOMPATIBILITIES Hazardous Decomposition Products:NONE

Waste Disposal Methods:DUST OR SCRAPE CREATED DURING FABRICATION OR DEMOLITION MUST BE DISPOSED ACCORDING TO NESHAP (40 CFR 61, SUBPART M). STATE AND LOCAL REGULATIONS MAY ALSO APPLY.

Disclaimer (provided with this information by the compiling ag

encies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.