

EASTMAN KODAK COMPANY -- 188 8742,VNF1/RVNP COLOR DEVELOPER,PART A-1 --
6750-00-965-4954

===== Product Identification =====

Product ID:188 8742,VNF1/RVNP COLOR DEVELOPER,PART A-1

MSDS Date:09/02/1987

FSC:6750

NIIN:00-965-4954

Kit Part:Y

MSDS Number: BFZWJ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Nu

m:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:SODIUM PHOSPHONATE

Fraction by Wt: 35-40%

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 55-65%

===== Hazar

ds Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Effects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.

===== First Aid Measures =====

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.
INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES CONTAINING CHEMICALS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H₂O SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORBENT, SHOVEL INTO METAL DRUMS:LG SPILL:DIKE W COMMERCIAL ABSORBENT, PUMP INTO COVERED DRUMS.

ORB W COMMERCIAL

ABSORBENT, SHOVEL INTO METAL DRUMS:LG SPILL:DIKE W COMMERCIAL ABSORBENT, PUMP INTO COVERED DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM CONTACT W/OXIDIZING MATERIALS.AVOID STRONG ACIDS.STORE IN COOL DRY PLACE.KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED.

Ventilation:MECHANICAL

L(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED
Protective Gloves:AS REQUIRED
Eye Protection:AS REQUIRED
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.
Supplemental Safety and Health
PART A1 OF A FIVE PART KIT KEY1:N1

===== Physical/Chemical Properties =====

HCC:B3
Boiling Pt:B.P. Text:>212F,>100C
Vapor Pres:17
Vapor Density:0.6
Spec Gravity:1.4
pH:10.2
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR, PALE YELLOW SOLUTION, AMMONIA ODOR
P
ercent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, STRONG ACIDS
Stability Condition to Avoid:EXCESSIVE HEAT
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATION
S.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular sit

uation.