View NSN Online: https://aerobasegroup.de/nsn/6750-00-965-4954

EASTMAN KODAK COMPANY -- 188 8742 VNF-1/RVNP COLOR DEVELOPER, PART B 6750-00-965-4954

Product ID:188 8742 VNF-1/RVNP COLOR DEVELOPER, PART B MSDS Date:04/14/2000 FSC:6750 NIIN:00-965-4954 Kit Part:Y MSDS Number: BFZWK === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Nu m:716-477-3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 Preparer's Name:NOT PROVIDED CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES Address:800 LEE RD Box:City:ROCHESTER State:NY ZIP:14650-3129 Country:US Phone:800-828-6203 CAGE:5K871

=======

===== Composition/Information on Ingredients ===========

Ingred Name:TERT-BUTYLAMINE BORANE CAS:7337-45-3 RTECS #:EO3900000 = Wt:100.

LD50 LC50 Mixture:ORAL LD-50 (RAT): 25 MG/KG Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EFFECTS OF EXPOSURE: INHALATION: HARMFUL IF INHALED. IF DIBORANE GAS IS LIBERATED AT CONCENTRATIONS ABOVE RECOMMENDED EXPOSURE LIMITS DUE TO CONTACT W **ITH A STRONG** OXIDIZER, ACID, OR WATER, IT MAY CAU SE RESPIRATORY TRACT IRRITATION, DROWSINESS, CHEST TIGHTNESS, COUGHING, WHEEZING, PULMONARY EDEMA, AND DEATH. EFFECTS MAY BE DELAYED. EYES: CAUSES IRRITATION. SKIN: CAUSES IRRITATION. HARMFUL IF ABSOR BED THROUGH SKIN. INGESTION: MAY BE FATAL IF SWALLOWED. MAY CAUSE CONVULSIONS. Explanation of Carcinogenicity:CARCINOGENICITY CLASSIFICATION (COMPONENTS PRESENT AT 0.1% OR MORE): - INTERNATIONAL AGENCY FOR **RESEARCH ON CAN** CER (IARC): NONE - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH): NON E - NATIONAL TOXICOLOGY PROGRAM (NTP): NONE - OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE Effects of Overexposure: INHALATION: IF DIBORANE GAS IS LIBERATED AT CONCENTRATIONS ABOVE RECOMMENDED EXPOSURE LIMITS DUE TO CONTACT WITH A STRONG OXIDIZER, ACID, OR WATER, IT MAY CAUSE RESPIRATORY TRACT IRRITATION, DROWSINE SS, CHEST TIGHTNESS, COUGHING, WHEEZING, **PULMONARY E** DEMA, AND DEATH. EFFECTS MAY BE DELAYED. EYES: CAUSES **IRRITATION. SKIN: CAUSES IRRITATION. INGESTION: MAY CAUSE** CONVULSIONS.

Medical Cond Aggravated by Exposure:NOT PROVIDED

First Aid:INHALATION: MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL ATTENTION. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LE AST 15 MINUTES WHILE REMOVING

CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION. WASH CONTAMINATED CLOTHING BEFORE REUSE. DESTROY OR THOROUGHLY CLEAN CONTAMINATED SHOES. INGESTION: INDUCE VOMITING AS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

Extinguishing Media:FLOOD WITH WATER.

Fire Fighting Procedures

:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. USE WATER WI TH CAUTION. MATERIAL REACTS WITH WATER. WATER MAY BE INEFFECTIVE IN FIGHTING THE FIRE. Unusual Fire/Explosion Hazard:CONTACT WITH WATER LIBERATES TOXIC GAS. ELEVATED TEMPERATURE CAN CAUSE DECOMPOSITION. POWDERED MATERIAL MAY

FORM EXPLOSIVE DUST-AIR MIXTURES.

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. AVOID GENERATION OF DUST. OTHERWISE, COLLECT UP AND PUT IN A SUITABLE CONTAINER. CLEAN SURFACE THOROUGHLY TO REMOVE RESIDUAL CONTAMINATION. Neutralizing Agent: NOT RELEVANT

Handling and Storage Precautions:STORE IN POLYETHYLENE CONTAINERS. DO NOT STORE IN GL

ASS. KEEP CONTAINER TIGHTLY CLOSED AND DRY. KEEP
AWAY FROM WATER, INCOMPATIBLE SUBSTANCES (SEE INCOMPATIBILITY SECTION). CONTENTS MAY DEVELOP PRESSU RE IF EXPOSED TO WATER. STORE IN A COOL PLACE. KEEP FROM CONTACT WITH OXIDIZING MATERIALS.
Other Precautions: AVOID CONTACT WITH EYES, SKIN, AND CLOTHING. AVOID BREATHING DUST. IF ACCIDENTALLY MIXED WITH A STRONG OXIDIZER, ACID OR WATER, DO NOT BREATHE GAS. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. KEEP F ROM ANY CONTACT WITH WATER. DO NOT ALLOW WATER TO GET INTO CONTAINER BECAUSE OF REA CTION. Respiratory Protection: RESPIRATORY PROTECTION: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS TO AN ACCEPTABLE LEVEL, AN APPROVED RESPIRATOR MUST BE WORN. RESPIRATOR TYPE: FULL-FACE POSITIVE-PRESSURE AIR- SUPPLIED. IF RESPIRATORS ARE USED. A PROGRAM SHOULD BE INSTITUTED TO ASSURE COMPLIANCE WITH OSH A STANDARD 29 CFR 1910.134. Ventilation: USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION OR OTHER ENGINEERING CONTROLS TO MAINTAIN AIRBORNE LEVELS TO AN ACCEPTABLE LEVEL. Protective Gloves:WEAR IMPERVIOUS GLOVES AND PROTECTIVE CLOTHING APPROPRIATE FOR RISK OF EXPOSURE Eye Protection: WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES). Other Protective Equipment: EYE BATH, WASHING FACILITIES, SAFETY SHOWER Work Hygienic Practices:NOT PROVIDED Supplemental Safety and Health STORE AN D SHIP SEPARATELY FROM OTHER PARTS OF THE KIT. ABBREVIATION: N/A=NOT APPLICABLE OR NOT AVAILABLE. N/K=UNKNOWN. N/P=NOT PROVIDED. N/R=NOT RELEVANT. N/D=NOT DETERMINED. N/E=NOT ESTABLISHED. CNS= CENTRAL NERVOUS SYSTEM. GI=GASTROINTESTINAL.

HCC:F8 NRC/State Lic Num:NOT RELEVANT Melt/Freeze Pt:=100.C, 212.F M.P/F.P Text:WITH DECOMPOSITION Decomp Temp:=100.C, 212.F Vapor Pres:NOT AVAILABLE Spec Gravity:0.87 pH:NOT AVAI LABLE Solubility in Water:DECOMPOSES. Appearance and Odor:WHITE SOLID (CRYSTAL). ODOR: AMINE. Corrosion Rate:NOT PROVIDED

Stability Indicator/Materials to Avoid:YES MATERIAL CAN REACT WITH WATER. PRESSURE MAY DEVELOP IN CONTAINER IF CONTENTS ARE EXPOSED TO WATER. CONTACT WITH ACID LIBERATES FLAMMABLE MATERIAL, TOXIC GAS. STRONG OXIDIZING AGENTS. CONTACT WITH WATER LIBERATES TOXIC GAS. Stability Condition to Avoid:E

XOTHERM ONSET TEMPERATURE: 100C
Hazardous Decomposition Products: DIBORANE GAS, HYDROGEN, CARBON
DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN

Toxicological Information:ACUTE TOXICITY DATA: ORAL LD-50 (RAT): 25 MG/KG DERMAL LD-50: 1-5 G/KG SKIN IRRITATION: MODERATE IRRITATION EYE IRRITATION: SLIGHT IRRITATION

Ecological:THIS MATERIAL HAS N OT BEEN TESTED FOR ENVIRONMENTAL EFFECTS.

Waste Disposal Methods:DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS. CONTRACT WITH A LICENSED CHEMICAL DISPOSAL AGENCY. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, FOLLOW LABEL WAR NINGS EVEN AFTER CONTAINER IS EMPTIED.

Transport Information:FOR TRANSPORTATION I NFORMATION REGARDING THIS PRODUCT CALL THE KODAK WORLDWIDE TRANSPORTATION HAZMAT HOT LINE: (716) 722-2400 BETWEEN 8 A.M. AND 5 P.M. (EASTERN STANDARD TIME), MONDAY THROUGH FRIDAY.

SARA Title III Information:CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR PART 372: NONE
Federal Regulatory Information:NOT PROVIDED
State Regulatory Information:MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: NONE - MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE ADVERSE REPRODUCTIVE EFFECTS: NONE

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoe

ver,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.