

EASTMAN KODAK COMPANY -- 187 9113,RP X-OMAT DEVLPR REPLNSHR,PART A --
6525-00-975-0611

===== Product Identification =====

Product ID:187 9113,RP X-OMAT DEVLPR REPLNSHR,PART A

MSDS Date:01/01/1985

FSC:6525

NIIN:00-975-0611

MSDS Number: BGBFQ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-477-3194

MSDS: 800-242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:POTASSIUM HYDROXIDE (SARA III)

CAS:1310-58-3

RTECS #:TT2100000

Fraction by Wt: 10.0%

OSHA PEL:C, 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9192

EPA Rpt Q

ty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:POTASSIUM SULFITE;CAS #10117-38-1; WT RANGE:10-15%
RTECS #:WT3530000
Fraction by Wt: 15.0%

Ingred Name:HYDROQUINONE (SARA III)
CAS:123-31-9
RTECS #:MX3500000
Fraction by Wt: 10.0%
OSHA PEL:2 MG/M3
ACGIH TLV:2 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:DIETHYLENE GLYCOL;CAS #111-46-6; % WT RANGE 1-5%
CAS:111-46-6
RTECS #:ID5950000
Fraction by Wt: 5.0%

Ingred Name:WATER;CAS #7732-18-5; % WT RANGE:55-60%
CAS:7732-18-5
RTECS #:ZC011000
0
Fraction by Wt: 60.0%

=====
===== Hazards Identification =====

Effects of Overexposure:EYES:LIQ CAUSES BURNS;SKIN:PROLONGD CONTCT
CAUSES IRRITATION.REPEATD CONTCT MAY CAUSE ALLERGY ACTION

=====
===== First Aid Measures =====

First Aid:GET MED ATTN INCASE OF EYE /SKIN IRRITATION OR BURNS.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighti

ng Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTD PERSONS.STOP LEAK W/O RISK.PROVIDE VENTILATION.ABSORB SM SPILL W/COMMERCIAL ABSORBENT & SHOVEL INTO METAL DRUM;LG SPILL:DIKE LIQ & PUMP INTO COVERD DRUM;MFR SPECIFIES NEUTRALIZE W/ SODIUM BISULFITE.FLUSH TO SEWER IAW EXISTING REGS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED
Other Precautions:THE ROUTINE USE OF A NON-ALKALINE(ACID)TYPE HAND CLEANER WILL HELP MINIMIZE THE POSSIBILITY OF ALLERGIC SKIN REACTION

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED
Ventilation:NO SPECIAL REQUIREMENTS W ADEQUATE VENT.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.
Supplemental Safety and Health
MSDS FM MFR DATED:07/30/80;PART A OF 3 PART PRODUCT;ALL PARTS NEEDED TO MAKE 20 GAL SOLUTION;PH OF PART A:11.6;SEE P/N IND B & C FOR PART B & C FOR PART B & C DATA,UNDER THIS NSN. KEY1;J6.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:>212F/100C
Vapor Pres:17
Vapor Density:0.6
Spec Gravity:1.30
Solubility in

Water:COMPLETE

Appearance and Odor:SLIGHTLY YELLOW-ODORLESS LIQUID

Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS,OXIDANTS.

Hazardous Decomposition Products:CO,CO*2,ETC.

===== Disposal Considerations =====

Waste Disposal Methods:PER MFR,INCINERATE,LANDFILL,OR FOLLOW STEPS ABOVE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.