

TUFF-KOTE CO, INC -- TUFF-KOTE,OIL-BASE SEALING COMPOUND -- 8030-00-975-0713

=====  
Product Identification  
=====

Product ID:TUFF-KOTE,OIL-BASE SEALING COMPOUND

MSDS Date:01/01/1985

FSC:8030

NIIN:00-975-0713

MSDS Number: BGBGK

=== Responsible Party ===

Company Name:TUFF-KOTE CO, INC

Address:210 SEMINARY AVE

City:WOODSTOCK

State:IL

ZIP:60098-3428

Country:US

CAGE:MO423

=== Contractor Identification =

==

Company Name:TUFF-KOTE CO INC

Address:210 SEMINARY AVE

Box:City:WOODSTOCK

State:IL

ZIP:60098-3428

Country:US

CAGE:15489

Company Name:TUFF-KOTE CO, INC

Address:210 SEMINARY AVE

Box:City:WOODSTOCK

State:IL

ZIP:60098-3428

Country:US

CAGE:MO423

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 25%.

OSHA PEL:100 PPM

Ingred Name:LEAD SULFATE (SARA III)

CAS:7446-14-2

RTECS #:OG437

5000  
Fraction by Wt: 0.5%  
OSHA PEL:SEE 1910.1025  
ACGIH TLV:0.15 MG PB/M3; 9192  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

===== Hazards Identification =====

Effects of Overexposure:SEVERE EYE IRRITATION, DRYING OF SKIN.EXCESSIVE  
INHALATION CAUSES HEADACHE,DIZZINESS,NAUSEA.

===== First Aid Measures =====

First Aid:EYE:IMMEDIATELY FLUSH W/WATER FOR AT LEAST 15 MINS. SKIN:WAS  
W/MILD SOAP AND WATER AND APPLY SKIN CREAM.  
INHALATION:REMOVE TO  
FRESH AIR AND CAL MD. APPLY ARTIFICIAL RESPIRATION IF NECESSARY.

===== Fire Fighting Measures =====

Flash Point:135F TOC (57C)  
Lower Limits:0.7  
Extinguishing Media:CO\*2, DRY CHEM, FOAM, (CLASS B EXTINGUISHERS)  
Fire Fighting Procedures:WATER SPRAY INEFF. USE WATER TO COOL  
CONTAINERS  
Unusual Fire/Explosion Hazard:IF WATER USEDFOG NOZ. PREF.KEEP  
CONTAINERS TIGHTLY CLOSED.ISOLATE FROM HEAT & IGNTN SOURCES,HOTSRF

===== = Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. RETURN  
MATERIAL TO CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND OPEN  
FLAME. USE W/ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED SKIN  
CONTACT.  
Other Precautions:DOT CLASSIFICATION:COMBUSTIBLE.

===== Exposure Controls/Personal Protection =====

Respirator

y Protection:USE IF SPRAYING. AVOID OVERSPRAY.(NIOSH/MSHA  
APP. RESP. PROT.)

Ventilation:GEN. DLTN/LOCAL EXH. IN VOL & PTTN TO KEEP TLV BELOW  
LIMITS

Protective Gloves:NOT REQ.

Eye Protection:AVOID EYE CONTACT

Supplemental Safety and Health

VAPOR DENSITY:HEAVIER THAN AIR.

===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:315 TO 380F

Vapor Pres:2

Evaporation Rate & Reference: