

ARCO PETROLEUM PRODUCTS CO -- DURO AW 46 (FORMALY DURO AW S-215) --
9150-00-993-6621

=====
===== Product Identification =====

Product ID:DURO AW 46 (FORMALY DURO AW S-215)

MSDS Date:01/01/1985

FSC:9150

NIIN:00-993-6621

MSDS Number: BGCFZ

=== Responsible Party ===

Company Name:ARCO PETROLEUM PRODUCTS CO

Emergency Phone Num:312-468-9300

CAGE:3T432

=== Contractor Identification ===

Company Name:ARCO PETRO

LEUM PRODUCTS COMPANY

Address:515 SOUTH FLOWER STREET

Box:City:LOS ANGELES

State:CA

ZIP:90071

Country:US

Phone:312-210-3000(CHEMTREC 800-424-9300)

CAGE:3T432

Company Name:ARCO PRODUCTS CO DIV OF ATLANTIC RICHFIELD CO

Address:333 S HOPE ST

Box:512570

City:LOS ANGELES

State:CA

ZIP:90071-0570

Country:US

Phone:213-486-0773/800-322-2726 INFO

CAGE:9V333

=====
===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT REFINED MINERAL OIL

Fraction by Wt: 99%

ACGIH TLV:5 MG/CUM

Ingred Name:ADDITIVE (PROPRIETARY COMPOSITION)

Fraction by Wt: 1%

===== Hazards Identification =====

Effects of Overexposure:EYE: IRRITATION.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MIN. SKIN: WASH WITH SOAP & WATER.
INGESTION: GIVE QUANTITIES OF WATER,INDUCE VOMITING,GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:410F/210C (D92

)

Extinguishing Media:DRY CHEM,CO*2;WATER & FOAM ARE EFFECTIVE BUT MAY CAUSE FROTH

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:MIST OR SPRAYS MAY BE FLAMMABLE AT TEMPS BELOW THE NORMAL FLASH POINT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. USE ABSORBENT MATERIAL SUCH AS CLAY OR DIATOMACEOUS EARTH TO CLEAN UP SPILL.

===== Handling and Sto

rage =====

Handling and Storage Precautions:STORE AWAY FROM OPEN FLAMES

Other Precautions:OIL SOAKED CLOTHING SHOULD BE REMOVED AND LAUNDERED,WASH SKIN WITH SOAP AND WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.

Ventilation:GENERAL

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GLASSES.

Supplemental Safety and Health

VISCOSITY: 200 SUS/100F/37C

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>600F/>315C

Vapor Pres:0.1

Vapor Density:>10

Spec Gravity:0.87

Evaporation Rate & Reference:>1 (ETHER)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER LIQUID - LUBE OIL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Hazardous Decomposition Products:CARBON MONOXIDE

===== Disposal Co

nsiderations =====

Waste Disposal Methods:COMPLY WITH LOCAL,STATE AND FEDERAL REUGLATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.