

VERSATEC(A XEROX CO). -- 4405-2 TYPE H, TYPE V80 TONER PEMIX -- 6850-01-008-0946  
===== Product Identification =====

Product ID:4405-2 TYPE H, TYPE V80 TONER PEMIX

MSDS Date:01/01/1987

FSC:6850

NIIN:01-008-0946

MSDS Number: BGCXJ

=== Responsible Party ===

Company Name:VERSATEC(A XEROX CO).

Address:2805 BOWERS AVE.

City:SANTA CLARA

State:CA

ZIP:95051

Info Phone Num:800-828-6571

Emergency Phone Num:7

16-422-2177

CAGE:MO494

=== Contractor Identification ===

Company Name:VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

Address:2710 WALSH AVE.

Box:City:SANTA CLARA

State:CA

ZIP:95051-0905

Country:US

Phone:716-422-2177 (XEROX CORP, NY)

CAGE:50804

Company Name:VERSATEC(A XEROX CO).

Address:2805 BOWERS AVE.

City:SANTA CLARA

State:CA

ZIP:95051

Phone:800-828-6571

CAGE:MO494

===== Composition/Information on Ingredients =====

Ingred Name:ISOPARAFFINIC PETROLEUM SOLVENT(90-95%),(CAS

#64742-48-9)  
Fraction by Wt: 92.5%  
ACGIH TLV:300 PPM

Ingred Name:METHACRYLATE CO-POLYMER(CAS#9011-15-8)  
Fraction by Wt: 5%  
OSHA PEL:3.5 MG/M3  
ACGIH TLV:3.5 MG/M3; 9192

=====  
Hazards Identification  
=====

Effects of Overexposure:ING:MAX RISK OF SEVERE RESPIR DISTRESS BY  
ASPIRATION;INH:ABNORMAL HEART RHYTHMS.RESPIRAT. ARREST.

=====  
First Aid Measures  
=====

First Aid:EYE:FLUSH W/COPIOUS AMOUNT OF WATER;SKIN:WASH WITH SO  
AP &  
WATER;INHALE:REMOVE TO FRESH AIR,GIVE ARTIFICIAL RESPIRATION IF  
NEEDED;ING:DILUTE STOMACH CONTENTS WITH SEVERAL GLASSES OF WATER.DO  
NOT INDUCE VOMITING.

=====  
Fire Fighting Measures  
=====

Flash Point:102-107F(TCC)  
Lower Limits:0.8  
Upper Limits:7  
Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*2O FOG.  
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H\*20 SPRAY TO COOL  
CONTR.  
Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDAN  
TS  
LIKE LIQ CHLORINE OR CONCENTRATED OXYGEN.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE IGNITION SOURCES.RECOVER FREE LIQUID  
USING AN ABOSRBANT MATERIAL(VERMICULITE,FIRE RETARDANT,SAWDUST,ETC)

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED,LOW FIRE  
RISK AREA. PROTECT FR HEAT,SHOCK KEEP CONTAINERS CLOSED.  
Other Precautions:AVOID BREATHING VAP

ORS.AVOID PROLONGED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE  
Ventilation:NORMAL  
Protective Gloves:NEOPRENE/NITRIL  
Eye Protection:NONE  
Other Protective Equipment:NONE  
Supplemental Safety and Health  
MSDS DATED 9-30-86. IT APPEARS TO HAVE A FORMULATION CHANGE. KEY1:F4

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:160-180C  
Vapor Pres:1  
Vapor Density:5  
Spec Gravity:0.78  
Evaporat  
ion Rate & Reference:0.25-0.45 BUAC=1  
Solubility in Water:IMMICIBLE  
Appearance and Odor:BLACK LIQ.,SLIGHT ODOR.  
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDANTS:LIQ CHLORINE,CONCEN OXYGEN,SODIUM HYPOCHLORI  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:FUMES,SMOKE,CO.

===== Disposal Considerations =====

Waste Disposal Methods:KE  
EP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &  
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
doc

ument should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.