

HOHMAN PLATING & MFG. INC. -- SURF-KOTE LOB-1899G CLASS B -- 9150-01-020-3610

=====
Product Identification
=====

Product ID: SURF-KOTE LOB-1899G CLASS B

MSDS Date: 10/01/1985

FSC: 9150

NIIN: 01-020-3610

MSDS Number: BGDZD

=== Responsible Party ===

Company Name: HOHMAN PLATING & MFG. INC.

Address: 814 HILLROSE AVE

City: DAYTON

State: OH

ZIP: 45404-1132

Country: US

Info Phone Num: 513-228-2191

Emergency Phone

Num: 513-228-2191

Preparer's Name: SCOTT WILSON

CAGE: DO354

=== Contractor Identification ===

Company Name: HOHMAN PLATING & MFG INC.

Address: 814 HILLROSE AVE.

Box: City: DAYTON

State: OH

ZIP: 45404-1132

Phone: 513-228-2191

CAGE: DO354

Company Name: HOHMAN PLATING AND MFG INC

Address: 814 HILLROSE AVE

Box: City: DAYTON

State: OH

ZIP: 45404-1132

Country: US

Phone: 937-228-2191

CAGE: 01094

=====
Composition/Information on Ingredients
=====

Ingred Name: GRAPHITE, CAS.

CAS: 7782-42-5

RTECS #: VV778000

0
Fraction by Wt: 35%.
OSHA PEL:15 MPPCF RDUST
ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:IRRITATION IS THE MAIN HAZARD. EYE
CONTACT REQUIRES FLUSHING WITH MUCH WATER AND A CONSULTATION WITH A
PHYSICIAN.
Explanation of Carcinogenicity:
NONE LISTED
Effects of Overexposure:LOCAL AND/OR SYSTEMIC IRRITATION.

=====
First Aid Measures
=====

First Aid:REMOVE FROM EXPOSURE. IF INGESTED DILUTE WITH WAATER TO WHICH
VINEGA OR LEMON JUICE HAS BEEN ADDED. FOR SKIN UTILIZE ORDINAATY
METHODS OF PERSONAL HYGIENE.

=====
Fire Fighting Measures
=====

Flash Point:"NOT APPLICABLE"
Extinguishing Media:"NOT APPLICABLE"
Fire Fighting Procedures:"NOT APPLICABLE"
Unusua
I Fire/Explosion Hazard:"NOT APPLICABLE"

=====
Accidental Release Measures
=====

Spill Release Procedures:CONTAIN THE SPILL. SCRAPE UP AND RECLAIM OR
ABSORB AND DISPOSE OF IN A WASTE CONTAINER. WASH WITH SOAP AND
DETEERGENT.
Neutralizing Agent:NO INFORMATION GIVEN ON MSDS BY SUPPLIER

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID CONTACT WITH THIS ALKALINE
MATERIAL. FOLLOW THE INSTRUCTIONS ON

THE LABEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:INDUSTRIAL HYGIENE EVALUATION. IF PROTECTION IS REQUIRED USE NIOSH APPROVED EQUIPMENT.

Ventilation:LOCAL EXHAUST:PREFERRABLE.

MECHANICAL(GENERAL)EXHAUST:ACCEPTABLE. SPECIAL AND OTHER EXHAUST:NONE

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER, APRON AND SHOE COVERING.

Work Hygienic Practices:DO NO

T EAT OR SMOKE WHERE THIS MATERIAL IS PRESENT.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:212F,100C

Spec Gravity:1.

Solubility in Water:MOST OF THIS MATER'L

Appearance and Odor:THIS IS A BLUE-BLACK LIQUID WITH A "WET" ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

ALKALI METALS

Stability Condition to Avoid:NO INFORMATION GIVEN ON

MSDS BY SUPPLIER

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:NEUTRALIZE TO PH ACCEPTABLE TO ENVIRONMENTAL AUTHORIES AND WASH INTO A CHEMICAL SEWER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of Ameri

ca in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.