

EASTMAN KODAK COMPANY -- 106 5895,FLEXCOLR BLCH II,PART A(POST 1987) --
6750-01-022-8410

===== Product Identification =====

Product ID:106 5895,FLEXCOLR BLCH II,PART A(POST 1987)

MSDS Date:01/29/1987

FSC:6750

NIIN:01-022-8410

Kit Part:Y

MSDS Number: BGFDP

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Nu

m:716-477-3194 FOR MSDS : 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 60-65%

Ingred Name:AMMONIUM BROMIDE

CAS:12124-97-9

RTECS #:BO9170000

F

raction by Wt: 20-25%

Ingred Name:AMMONIUM ACETATE (SARA III)

CAS:631-61-8

RTECS #:AF3675000

Fraction by Wt: 10-15%

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 1-5%

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:I

RRITATING;SKIN:LOW

HAZARD;INHALATION:LOW HAZARD

Explanation of Carcinogenicity:NOT LISTED

Effects of Overexposure:SEE HEALTH HAZARDS

Medical Cond Aggravated by Exposure:NONE NOTED BY MANUFACTURER

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH PLENTY OF WATER; SKIN: FLUSH WITH SOAP &
WATER; INHALATION: REMOVE TO FRESH AIR; INGESTION: DRINK ONE OR TWO
GLASSES OF WATER, SEEK MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, ALCOHOL
FOAM

Fire Fighting Procedures:WEAR SELF-CONTAINED & PROTECTIVE CLOTHING TO
PREVENT CONTACT WITH SKIN & EYES.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER.
FOLLOW WITH

SECONDARY WASTE WATER TREATMENT

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM CONTACT WITH OXIDIZING MATERIALS.

===== Exposure Controls/Personal Protection =====

Ventilation:GOOD GENERAL VENTILATION
Protective Gloves:AS REQUIRED
Eye Protection:SAFETY GLASSES
Work Hygienic Practices:STANDARD HYGENIC PRACTICES
Supplemental Safety and Health
THIS CAT #106-5895 IS REPLACEMENT FOR 190-1685 WHICH WAS DISCONTINUED
IN MAY,1987. THIS NEW CATALOG CONSISTS OF 2-PART A,& B. THIS IS PART-A. FOR PART-B, SEE P/N IND G. PART-A IS NOT REGULATED & PT-B IS CORROSIVE LIQUID. PART A,FLEXICOLOR BLEACH II SOLUTION NO:5308; KEY1=N1.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:>212F,>100C
Vapor Pres:18
Vapor Density:0.6
Spec Gravity:1.148
pH:5.84
Evaporation Rate & Reference:0.4(BU AC=1)
Solubility in Water:COMPLETE
Appearance and Odor:COLORLESS
CLEAR SOLUTION;SLIGHT ACETIC ODOR
Percent Volatiles by Volume:65

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:HEAT,OPEN FLAMES
Hazardous Decomposition Products:AMONIA AND OXIDES OF CARBON IN COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE,TREATMENT,OR DISPOSAL MAY BE SUBJECT TO FEDERAL,STATE OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.