

BORDEN, CONSUMER PRODUCTS DIVISION -- KRYLON 1605 -- 8010-01-027-4852

===== Product Identification =====

Product ID:KRYLON 1605

MSDS Date:12/04/1986

FSC:8010

NIIN:01-027-4852

MSDS Number: BGFRN

=== Responsible Party ===

Company Name:BORDEN, CONSUMER PRODUCTS DIVISION

Address:180 E BROAD ST

City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

Emergency Phone Num:614-431-6600

CAGE:EO239

=== Contractor I

dentification ===

Company Name:BORDEN INC

Address:180 E BROAD ST

Box:208

City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

Phone:614-225-6124

CAGE:07982

Company Name:BORDEN, CONSUMER PRODS. DIV., DIV. OF BORDENS INC.

Address:180 EAST BROAD STREET

Box:City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

Phone:614-431-6680

CAGE:EO239

Company Name:CONSOLIDATED CONTROLS CORPORATION

CAGE:09790

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA III)

CAS:67-64-

1

RTECS #:AL3150000
Fraction by Wt: 30-50%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 1-5%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 15-30%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:7
8-93-3
RTECS #:EL6475000
Fraction by Wt: 15-30%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 1-5%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACEDIC ACID, 2-METHOXY-1-METHYLETHYL ESTER.
CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 5-15%

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3

RTECS #:XS5250000
Fraction by Wt: 1-5%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5-15%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IA
RC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: MAY BE HARMFUL. LIQUID OR
VAPOR CAN CAUSE IRRITATION OF NOSE, THROAT AND LUNGS. SKIN: CAUSES
IRRITATION. EYES: CAUSES IRRITATION.
Effects of Overexposure:CENTRAL NERVOUS SYSTEM DEPRESSION, HEADACHE,
DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND ASPHYXIATION.
Medical Cond Aggravated by Exposure:SKIN & LUNG DISORDERS.

===== First Aid Measures =====

First Aid:SKIN: IMMEDIATELY FLUSH WITH
WATER, IF IRRITATION PERSISTS,
GET MEDICAL HELP. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES,
GET MEDICAL ATTENTION. INGESTION: DILUTE BY DRINKING LARGE
QUANTITIES OF WATER. GET MEDICAL ATTENTION IMMEDIATELY.
INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR. IF
BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:N/R (AEROSOL)
Extinguishing Media:DRY CHEMICAL, FOAM OR CO₂.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE AS EXTINGUISHING MEDIA, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL. WEAR NIOSH APPROVED SCBA.

Unusual Fire/Explosion Hazard:EXPOSURE TO HIGH TEMPERATURE MAY CAUSE BURSTING. AVOID RADIATORS, STOVES, DIRECT SUNLIGHT, OR OTHER HEAT SOURCE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL & REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURES OVER 120F.

Other Precautions:IF AIRBORNE CONTAMINATES ARE GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, SUFFICIENT VENTILATION IN VOLUME AND AIR FLOW PATTERNS SHOULD BE PROVIDED TO KEEP AIR CONTAMINANT

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION. SELECT RESPIRATOR IN ACCORDANCE WITH OSHA 29 CFR 1910.134 OR OTHER APPLICABLE STANDARDS OR GUIDE LINES.

Ventilation:LOCAL EXHAUST VENTILATION RECOMMENDED TO MINIMIZE EMPLOYEE EXPOSURE.

Protective Gloves:IMPERVIOUS GLOVES AS REQUIRED

Eye Protection:GOGGLES WHERE CONTACT IS LIKELY

Other Protective Equipment:APRON & FULL LENGTH WORK CLOTHING.

Work Hygienic Practices:HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES. AVOID UNNECESSARY EXPOSURE & WASH THOROUGHLY.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>1

Spec Gravity: