

UNION OIL COMPANY OF CALIFORNIA(MFR)CHEM.COMM(DIST -- QPL TEST#MG-356 MP GEAR
LUBE LS 75 W. -- 9150-01-035-5390

=====
Product Identification
=====

Product ID:QPL TEST#MG-356 MP GEAR LUBE LS 75 W.

MSDS Date:01/01/1987

FSC:9150

NIIN:01-035-5390

MSDS Number: BGGHZ

=== Responsible Party ===

Company Name:UNION OIL COMPANY OF CALIFORNIA(MFR)CHEM.COMM(DIST

Emergency Phone Num:(213)664-2121

CAGE:5W523

==

= Contractor Identification ===

Company Name:76 PRODUCTS CO

Address:1201 W 5TH ST

Box:City:LOS ANGELES

State:CA

ZIP:90017

Country:US

Phone:213-977-7589

CAGE:23034

Company Name:UNION OIL COMPANY OF CALIFORNIA

Address:1345 NORTH MEACHAM ROAD

City:SCHAUMBURG

State:IL

ZIP:60196

Country:US

Phone:800-438-2968

CAGE:5W523

=====
Composition/Information on Ingredients
=====

Ingred Name:LUBRICATING OIL (HYDROCARBON MIXTURE) (MFR SUGGEST TLV AS
OIL MIST)

Fraction by Wt: 100%

ACGIH TL

V:5MG/CUM(OILMIST)

===== Hazards Identification =====

Effects of Overexposure:IRRITATING TO EYES,SKIN AND RESPIRATORY TRACT.SKIN:PROLONGED CONTACT MAY RESULT IN DERMATITIS.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:>200F/93C
Extinguishing Media:DRY CHEMICAL,CO*2,FOAM.
Fire Fighting Procedures:USE NIOSH APPROVED RESPIRATOR FOR FIRES AND IN CONFINED AREA
Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL SURFACES AND OTHER METAL SURFACES.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION.KEEP IGNITION SOURCES AWAY.ABSORB SPILLED MATERIAL INTO SUITABLE ABSORBENT AND RECOVER FOR PROPER DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT AND OPEN FLAMES.KEEP CONTAINER CLOSED WHEN NOT IN USE.
Other Precautions:AVOID CONTACT WITH SKIN AND EYES.DO NOT BREATHE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESP

IRATOR FOR ORGANIC
VAPORS.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 550F/288C

Vapor Density:>1.0

Spec Gravity: